

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto	
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021	
		3CX400sq.mm (51 GI Wires - 4mm Dia)				
		11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	31.12.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)				
		4 Core, 2.5 Sqmm, 21 No GI Wires (1.4mm)	29.06.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		4 Core, 6 Sqmm, 25 No GI Wires (1.6mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)				
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)				
		3.5C x 185Sq mm, (28 GI Strips - 4.0 x 0.8mm)				
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		3.5C x 150Sq mm, (25 GI Strips - 4.0 x 0.8mm)				
3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)						
3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)						
4C x 10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)						
1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010						
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021			
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs						
2	M/s Polycab India Ltd., (Formerly Polycab Wires Limited) 74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore - 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		11kV 3C x 95 sq. mm. (54 GI Wires - 2.5mm dia)	31.08.2025	GM(Q,S&S)DGM -3)/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)	20.12.2023 GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021	
		11kV 3x240 sq. mm (55 GI Wires - 3.15mm dia)				
		11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		3CX400sq.mm (51 GI Wires - 4mm Dia)	02.01.2023	GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021		
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		6 Sqmm, 2Core,(24 GI wire - 1.4mm)				
		10Sqmm, 2Core,(9GI Strips - 4.0 x 0.8mm)				
		10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)				
		16 Sqmm, 2Core,(9 GI Strips - 4.0 x 0.8mm)				
		16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)				
25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm)						
25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)						

		25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)	05.10.2022		05.10.2022 GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dt:20.12.2021
3	M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 [E-mail:venkataraju.kt@havells.com]	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3C x 400 Sq mm, (51 GI Wires - 4mm Dia) 1.1kV LT, XLPE, PVC exutrated Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 2C x 10 sq mm (9 GI Strips - 4.0 x 0.8mm) 4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm) 3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm) 4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm) 3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm) 3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm) 3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm) 3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	17.03.2022 23.01.2022 12.07.2024 20.12.2021 10.01.2024 20.12.2021 20.07.2022 31.01.2024 20.12.2021 10.01.2024 29.01.2024 11.01.2024 10.01.2024	GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-28 dated:17.05.2017 (Subject revalidation every year) GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021 20.12.2021 09.02.2023 20.12.2021 20.07.2022 09.02.2023 21.12.2021 09.02.2023 09.02.2023 09.02.2023 09.02.2023
4	M/s Dynamic Cables Ltd., H-581-A-592-A, Road No:6. VKI Area, Jaipur - 302013	11kV, 3 x 95 sq. mm HT XLPE UG cable 11kV, 3 x 240 sq. mm HT XLPE UG cable 11kV, 3 x 400 sq. mm HT XLPE UG cable	12.09.2022	GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-163 dated:07.10.2017 (Subject revalidation every year)	GM(QS&S)/DGM(E)-3/BC-11/20-21/CYS-163 dt:09.11.2020
5	M/s Insucon cables & Cond(P) Ltd., # 314-A, 3rd Floor, City centre, Sansar chandra Road, Jaipur-302001, Raj(Factory Unit: Road No:5A, F-61-63, Bindayaka Industrial Area, Jaipur-12)	Armoured LT UG Cable 1.1class 4C x 16sq mm 3.5C x 95sq mm 3.5C x 240sq mm 3.5C x 400sq mm 4C x 25sq mm PVC Insulatec & Unsheathed Aluminium Wires, Single Core Multistrand 1.1kV class 1C x 16 sqmm 1C x 50 sqmm 1C x 95 sqmm 1C x120 sqmm 1C x 150 sqmm 1C x 185 sqmm 1C x 240 sqmm	30.06.2022 30.06.2022	GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-72 dated:11.07.2017 (Subject revalidation every year)	30.06.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-169 dt:12.11.2020
6	M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868/869, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085145, 7230085146 E-mail:bhiwadi@gemscab.com ,	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia)	05.07.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-32 dt:05.07.2021 (Subject to revalidation)	

	pathredi@gemscab.com	3CX400sq.mm (51 GI Wires - 4mm Dia)		(Subject to revalidation once in 2 years)		
7	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai - 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East - 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.04.2024	GM(Q,S&S)DGM -3/BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)	16.08.2023 GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dtd:16.08.2021	
		2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm))				
		4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm))				
		19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm))				
		2 Core, 6 Sq mm, (24 No GI Wires (1.4mm))	22.04.2024	GM(QS&S)/DGM-3/BC-11/19-20/CYS-116 dtd:18.09.2019	16.08.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021	
		4 Core, 16 Sq mm, (30 No GI Wires (1.6mm))				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
2C x 6 Sq mm,(24 GI wire - 1.4mm)						
4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm)	22.04.2024	GM(QS&S)/DGM-3/BC-11/19-20/CYS-116 dtd:18.09.2019	16.08.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:16.08.2021			
3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm)						
3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)						
8	M/s Torrent Cables Limited, Yoginagar, Mission Road, Nadiad - 387002 Changed the Company name to : M/s Torrent Power Limited, Yognagar, Mission Road, Nadiad - 387002 , Gujarat	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	05.10.2022	GM(QS&S)/DGM-3/BC-11/19-20/CYS-116 dtd:18.09.2019	05.10.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	20.05.2024		19.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021	
9	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkatta-700091. Works unit 1: IDOCD centre, khursha-752054, Odisha Works unit 2: Nandanagar Industrial Estate, Kashipur-244713, Uttarakhand E-mail: info@guptapower.com/ rhino@guptapower.com Ph No:91-33-40657348	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)		
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)				
		3CX400sq.mm (51 GI Wires - 4mm Dia)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)		
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975				
185Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)	30.05.2023					
240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)						
400Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)						
10	M/s KEI Industries Ltd, Okhla industrial Area Phase-1, New Delhi Factory Unit: SP-919/920/922, RIICI Industrial Area, Ph.III, Bhiwadi Distt. Atwar-3010109	Armoured XLPE insulated LT UG Cable 1.1kV Class		GM(QS&S)/DGM-3/BC-11/17-18/CYS-137 dtd:20.09.2017	GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021	
		10 Sqmm, 4 Core	29.12.2021			
		16 Sqmm, 2 Core	17.08.2022			
		16 Sqmm, 4 Core	28.12.2021			
		25 Sqmm, 4 Core	03.01.2022			
		35 Sqmm, 3.5 Core	17.08.2022			17.08.2022
		50 Sqmm, 3.5 Core				
		70 Sqmm, 3.5 Core				
		95 Sqmm, 3.5 Core				
		150 Sqmm, 3.5 Core				
		185 Sqmm, 3.5 Core				
		240 Sqmm, 3.5 Core				
		300 Sqmm, 3.5 Core	22.06.2022			22.06.2022
		400 Sqmm, 3.5 Core	18.07.2022			18.07.2022
		11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975				
3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia)	29.06.2025 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/20-21/CYS-56 dtd:03.07.2020	07.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021			
3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia)						
3x400sq mm (51 GI wires - 4mm Dia)	10.07.2022		10.07.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021			

11	M/s Finolex Cables Limited, 26/27, Mumbai Pune Road, Pimpri, Pune-411 018	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3Cx95sq.mm (54 GI Wires - 2.5mm Dia)	27.11.2023 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/19-20/CYS-188 dtd:01.01.2020			
12	M/s KEC International Limited(Cables Division), Survey No:803, Village: Godampura Taluka - Salvi Dist, Vadodara - 391520.	11kV, 3 Core, HTUG Cable fwith pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3Cx95 Sqmm, (54 GI Wires - 2.5mm Dia)	03.01.2022	GM(QS&S)/DGM-4/BC-11/18-19/CYS-27 dtd:28.05.2017	03.01.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-218 dtd:11.01.2021		
		3Cx240 Sqmm, (55 GI Wires - 3.15mm Dia)					
		11kV 3 x 400 sq.mm(51 GI Wires - 4mm Dia)					
				16 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (11 GI Strips - 4.0 x 0.8mm)	08.01.2022	GM(QS&S)/DGM-3/BC-11/20-21CYS-217 dtd:11.01.2021	
			25 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (12 GI Strips - 4.0 x 0.8mm)				
			25 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (13 GI Strips - 4.0 x 0.8mm)				
			50 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (16 GI Strips - 4.0 x 0.8mm)				
			50 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (17 GI Strips - 4.0 x 0.8mm)				
	95 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (21 GI Strips - 4.0 x 0.8mm)						
	240 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (30 GI Strips - 4.0 x 0.8mm)						
13	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase - II, IDA, Chelapally, Hyderabad - 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)			
		10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)					
		16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)					
		25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)					
		25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)					
		35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)					
		50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)					
		70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)					
		95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)					
		120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)					
		150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)					
		185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)					
		300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm)					
400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)							
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	13.12.2023				
		10Core, 2.5 Sqmm, 28 No GI Wires (1.6mm)					
14	M/s Laser power & Infra Pvt Ltd, 4A, Pollock street, 3rd floor, Kolkata-700001 (Unit-1: Biprannapara, Jain complex, P.S. Domjur, Hawrah-711411, Unit II: NH-6, Poly Park, Dhulaguri, Howrah-711302)	11kV HT XLPE UG cable (Round & Flat Armour) 3C x 400sq mm	09.08.2022				
		1.1kV LT XLPE UG Cable 3.5C x 240sq mm	14.09.2022	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	13.03.2021 GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-225 dated:13.03.2020		
		4C x 16sq mm	14.09.2022				
		4C x 10sq mm					
		4C x 50sq mm					
		4C x 6sq mm					
		4C x 25sq mm					
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				05.07.2024	
		300Sq mm, 3.5Core (32GI Strips - 4.0 x 0.8mm)					
16	M/s Apar Industries limited, (Unit Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 39000 (Factory Unit: Plot no: 158/163, GIDC, Umergaon Dist, Valsad, Gujrarat - 396171) (Ph.No91(080)23443932/9986049678 email-kr.sanjay@apar.com	6.35/11kV HT XLPE UG Cable	30.07.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-140 dated:15.10.2020 (subject to revalidation every year)			
		3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable					
17	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi - 110040 Ph No:011-27318598,	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020			
		2C x 10 sqmm					
		4C x 10sq mm					
		4C x 16sq mm					
		4C x 25sq mm					
		4C x 50sq mm					
		4C x 95sq mm					
		3.5C x 50sq mm					
		3.5C x 70 sq mm					
		3.5C x 95 sq mm					
		3.5C x 120 sq mm					
		3.5C x 150sq mm					
		3.5C x 240sq mm					
		04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021					

22	M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080-26662172, 26860166)	PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021		
		PVC Wire - 50Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs				
		PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs				
		PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs				
		PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs				
		PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs				
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)				
		2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021		
		4Core, 2.5Sqmm, 21 No GI Wires (1.4mm)				
		4Core, 6Sqmm, 25 No GI Wires (1.6mm)				
		4 Core, 10Sqmm, 28 No GI Wires (1.6mm)				
		19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)				
		1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1,				
		50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021		
		16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm)				
25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm)						
1.1kV LT, XLPE Copper/Aluminium UG cable IS-7098 Part - 1						
50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021				
70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)						
95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)						
185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm)						
240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)						
400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)						
16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)						
11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	19.08.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year)	19.12.2022 GM(Q,S&S)DGM -3)/BC-11/20-21/cys-193 dated:21.12.2020			
(54 GI Wires - 2.5mm Dia)						
(55 GI Wires - 3.15mm Dia)						
(51 GI Wires - 4mm Dia)						
1.1kV class HR (Heat Resistant) PVC Insulated & Sheathed Aluminium Single Core Wires as IS- 694:2010	29.07.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-50 dtd:29.07.2021				
2.5sq mm						
1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheath armoured UG LT cable as per IS-1551 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as pere IS - 3975						
50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)						
240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)						
24	M/s Bonton Cables India Pvt Ltd Registered Office: Epitome Building No:05, 18th Floor, Tower -B, DLF Cyber City, Gurugram - 122001 (HR) Factory Unit: (Unit-II), A-6 (A), Kaharani Industrial area, Bhiwadi-301019 (Rajasthan) Contact No: 8130299032,8130299001, 8130299003	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1551 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as pere IS - 3975	29.07.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-51 dtd:29.07.2021		
		120Sq mm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)				
		185Sq mm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)				
240Sq mm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)						
M/s Vikas Cable Company, No.13, Haidarabab Dalhi - 510088	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as per IS - 3975					
	50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)					

25	वि.के.ए.सी. - 110000 Contact No: 91-11-27495529 E-mail:info@vikascable.com	400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm) 1.1kV Class HR (Heat Resistant) PVC Insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS-694: 2010 PVC Wire - 50 Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs	07.08.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-58 dtd: 07.08.2021	
26	M/s Rotoplast Wires and Cables, Gala No: 3 & 4, Nr. Shri Ganesh Industrial Estate, Beside Green Masjid, Farmer Talao, Vasai Pata, Vasai (E), Dist. Palghar - 401208 Contact No: 9986672160 Email:rotoplastcables@gmail.com	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as pere IS - 3975 10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5 Core, (14 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm) 1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2 Core, 2.5 Sqmm, (18 No GI Wires (1.4mm)) 4 Core, 2.5 Sqmm, (21 No GI Wires (1.4mm)) 19 Core, 2.5 Sqmm, (36 No GI Wires (1.6mm))	24.09.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-92 dtd: 24.09.2021	
		24.09.2022			
27	M/s Gloster Cables Limited, Registered Office: No.183/184, (5-3-370 to 372A) 2nd Floor, Above Mody Motors, Rahrtrapathi Road, Secunderabad-500003 Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 Ph No: 9180-22129305, 91-8454250511/12, 250769/71 Email:gclbanglore@glostercable.com, info@glostercable.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part 2)	20.08.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-127 dtd: 26.11.2021 (subject to revalidation once in 2 years)	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)			
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3CX400sq.mm (51 GI Wires - 4mm Dia)			
28	M/s Karnataka Industries, Sy No.130, Shed A-4, Machohalli Industrial Area, Magadi Road, Bangalore - 560091 Contact No: 9902068381 E-mail: bristolcables@yahoo.com	1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010 PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	30.05.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-128 dtd: 30.11.2021	
29	M/s Paragon Power cable Ltd., Plot No: 60, Phase -1, HSIIDC Industrial Estate, Kundli, Sonipat, Haryana - 131028 Contact No: 91-9810049100 & 9811025711 E-mail: sales@paragoncables.com	1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average ±5% and resistivity 140hms/Kms (Max) as per IS-3975 240 sqmm, 3.5 Core (30 GI Strips - 4.0x0.8mm) 16 sqmm, 4 Core (11 GI Strips - 4.0x0.8mm)	30.12.2025	GM(QS&S)/AE/BC-11/21-22/CYS-145 dtd: 31.12.2021 (Subject to first revalidation dated before 30.12.2022 and then it will be revalidated once in 2 years)	