

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto	
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(QS&S)/DGM-3/ BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021	
		3CX400sq.mm (51 GI Wires - 4mm Dia)				
		11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	31.12.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)				
		4 Core, 2.5 Sqmm, 21 No GI Wires (1.4mm)	29.06.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		4 Core, 6 Sqmm, 25 No GI Wires (1.6mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)				
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)				
		3.5C x 185Sq mm, (28 GI Strips - 4.0 x 0.8mm)				
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		3.5C x 150Sq mm, (25 GI Strips - 4.0 x 0.8mm)				
		3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)				
		3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)				
		4C x 10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)				
1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010						
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021			
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs						
2	M/s Polycab India Ltd., (Formerly Polycab Wires Limited) 74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore – 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		11kV 3C x 95 sq. mm. (54 GI Wires - 2.5mm dia)	31.08.2025	GM(Q,S&S)DGM -3/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)	20.12.2023 GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021	
		11kV 3x240 sq. mm (55 GI Wires - 3.15mm dia)				
3	M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868/869, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085145, 7230085146 E-mail:bhiwadi@gemscab.com .	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		3CX95sq.mm (54 GI Wires – 2.5mm Dia)				
		3CX240sq.mm (55 GI Wires – 3.15mm Dia)	05.07.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-32 dtd:05.07.2021 (Subject to revalidation once in		

	pathredi@gemscab.com	3CX400sq.mm (51 GI Wires – 4mm Dia)		2 years)	
4	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai – 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East – 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.04.2024	GM(Q,S&S)DGM -3)/ BC- 11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)	16.08.2023 GM(QS&S)/DGM-3/BC- 11/21-22/CYS-67 dtd:16.08.2021
		2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm))			
		4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm))			
		19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm))			
		2 Core, 6 Sq mm, (24 No GI Wires (1.4mm))			
		4 Core, 16 Sq mm, (30 No GI Wires (1.6mm))	22.04.2024	GM(QS&S)/DGM-3/BC- 11/20-21/CYS-227 dtd:21.01.2021	
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		2C x 6 Sq mm,(24 GI wire - 1.4mm)			
4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm)	22.04.2024	GM(QS&S)/DGM-3/BC- 11/21-22/CYS-67 dtd:16.08.2021			
3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm)					
3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)					
5	M/s Torrent Cables Limited, Yoginagar, Mission Road, Nadiad - 387002 Changed the Company name to M/s Torrent Power Limited, Yoginagar, Mission Road, Nadiad - 387002 , Gujarat	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	20.05.2024		19.01.2023 GM(QS&S)/DGM-3/BC- 11/20-21/CYS-227 dtd:21.01.2021
		3CX400sq.mm (51 GI Wires - 4mm Dia)			
6	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkatta-700091. Works unit 1: IDOCD centre, khursha-752054, Odisha Works unit 2: Nandanagar Industrial Estate, Kashipur-244713, Uttarakhand E-mail: info@guptapower.com/ rhino@guptapower.com Ph No:91-33-40657348	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21- 22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		3CX95sq.mm (54 GI Wires – 2.5mm Dia)			
		3CX240sq.mm (55 GI Wires – 3.15mm Dia)			
		3CX400sq.mm (51 GI Wires – 4mm Dia)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21- 22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975			
		185Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)			
240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)	30.05.2023				
400Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)					
7	M/s KEI Industries Ltd, Okhla industrial Area Phase-1, New Delhi Factory Unit: SP-919/920/922, RHICO Industrial Area, Ph:III, Bhiwadi Distt. Alwar-301019, Rajasthan. Tel No: 01493-220106/221731 & 080- 23466260/23466255 Email: mumbai@kei-ind.com, bhiwadi@kei- ind.com & banglore@kei-ind.com	11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975	29.06.2025 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/20- 21/CYS-56 dtd:03.07.2020	07.01.2023 GM(QS&S)/DGM-3/BC-11/20- 21/CYS-214 dtd:08.01.2021
		3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia)			
		3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia)	24.11.2022	GM(QS&S)/DGM-3/AE/ BC- 11/22-23/CYS-14 dtd: 24.05.2022	
		3x400sq mm (51 GI wires - 4mm Dia)			
		1.1kV LT, XLPE, PVC exutruded Inner Seath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	24.11.2022	GM(QS&S)/DGM-3/AE/ BC- 11/22-23/CYS-14 dtd: 24.05.2022	
		2C x 16 Sq mm (9 GI Strips - 4.0 x 0.8mm)			
		4C x 10 Sq mm (10 GI Strips - 4.0 x 0.8mm)			
4C x 25 Sq mm (13 GI Strips - 4.0 x 0.8mm)					

		3.5C x 50 Sq mm (16 GI Strips - 4.0 x 0.8mm)			
		3.5C x 70 Sq mm (18 GI Strips - 4.0 x 0.8mm)			
		3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)			
		3.5Cx 150 sq mm (25 GI Strips - 4.0 x 0.8mm)			
		3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)			
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)			
		3.5C x 300 Sq mm (32 GI Strips - 4.0 x 0.8mm)			
		3.5C x 400 Sq mm (39 GI Strips - 4.0 x 0.8mm)			
8	M/s Finolex Cables Limited, 26/27, Mumbai Pune Road, Pimpri, Pune-411 018	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia)	27.11.2023 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/19-20/CYS-188 dtd:01.01.2020	
9	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase - II, IDA, Chelapally, Hyderabad - 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm) 16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm) 1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 10Core, 2.5 Sqmm, 28 No GI Wires (1.6mm)	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	
			13.12.2023		
10	M/s LKB Engineering Private Limited., Registered Office: 204&205, Shivam House, Karpura, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Distt. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 300Sq mm, 3.5Core (32GI Strips - 4.0 x 0.8mm)	05.07.2024	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)	
11	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi - 110040 Ph No:011-27318598, E-mail:info@primecableindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable 2C x 10 sqmm 4C x 10sq mm 4C x 16sq mm 4C x25sq mm 4C x 50sq mm 4C x 95sq mm 3.5C x 50sq mm 3.5C x 70 sq mm 3.5C x 95 sq mm 3.5C x 120 sq mm 3.5C x 150sq mm 3.5C x 240sq mm 1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires 1C x 16 sqmm 1C x 25 sqmm 1C x 35 sqmm 1C x50 sqmm 1C x 70 sqmm 1C x 95 sqmm 1C x 120 sqmm 1C x 150 sqmm 1C x 185 sqmm 1C x 240 sqmm	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021 04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021
12	M/s Shanti Insulated Cable Co., C/o. Arihant Cable Corporation, No:B-24/1,	2C x 4sq mm to 3.5C x 400sq mm PVC Insulated and sheathed armour cable with Aluminium conductor	12.03.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-06 dated:13.04.2018	12.03.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-201

12	JHILMIL Industrial Area, Shahdara, Delhi - 110095 (Ph No:9311177331)	2Cx 0.5sq mm to 4C x 185sq mm PVC insulated and sheathed flexible cable of copper conductor	12.05.2020	12/05/2020 dated:12.05.2020 (Subject revalidation every year)	12/05/2020 dated:23.12.2020
13	M/s Keli Flex Cables, C/o. Aribant Cable Corporation, No: A-34, 2nd Floor, Jhimil, Indl. Area, Shadara, Delhi - 110095.	1C x 0.5sq mm to 1C x 400sq mm PVC Insulated sheathed flexible cable with copper conductor 2C x 0.5sq mm to 24C x 0.5sq mm PVC Insulated Unsheathed flexible cable with copper conductor	23.01.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-07 dated:13.04.2018 (Subject revalidation every year)	23.01.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-183 dated:09.12.2020
14	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 40 29702652, 29702657 E-mail: info@spm cables.in	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3C x 400 Sqmm (51 GI Wires - 4mm Dia) 1.1kV LT, XLPE PVC exutrated Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring stripthickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm) 185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm) 400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)	06.12.2025	GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-129 dated:07.12.2021	
		1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010 PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs PVC Wire - 50Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs 1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	

15	M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080-26662172, 26860166)	4Core, 2.5Sqmm, 21 No GI Wires (1.4mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021			
		4Core, 6Sqmm, 25 No GI Wires (1.6mm)					
		4 Core, 10Sqmm, 28 No GI Wires (1.6mm)					
		19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)					
		1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1,					
		50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021			
		16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm)					
		25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm)					
		1.1kV LT, XLPE Copper/Aluminium UG cable IS-7098 Part - 1					
		50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021			
		70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)					
		95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)					
		185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm)					
		240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)					
		400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)					
16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)							
11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)							
(54 GI Wires - 2.5mm Dia)	19.08.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year)	19.12.2022 GM(Q,S&S)DGM -3)/BC-11/20-21/cys-193 dated:21.12.2020				
(55 GI Wires - 3.15mm Dia)							
(51 GI Wires - 4mm Dia)							
16	M/s Vikas Cable Company, No.13, Haiderpur Delhi - 110088 Contact No: 91-11-27495529 E-mail:info@vikascable.com	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as per IS - 3975					
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)	24.12.2027	GM(QS&S)/DGM(EI)-3/BC-11/21-22/CYS-167 dtd:21.02.2022 (Subject to first revalidation dated before 17.02.2023 and then it will be revalidated once in 2 years)			
		25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm)					
		70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm)					
		95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)					
		120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)					
		150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm)					
		185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)					
240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)							
17	M/s Gloster Cables Limited, Registered Office: No.183/184, (5-3-370 to 372A) 2nd Floor, Above Mody Motors, Rahtrapathi Road, Secunderabad-500003 Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 Ph No: 9180-22129305, 91-8454250511/12, 250769/71 Email-gclbanglore@glostercable.com, info@glostercable.com	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)					
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	20.08.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-127 dtd: 26.11.2021 (subject to revalidation once in 2 years)			
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)					
3CX400sq.mm (51 GI Wires - 4mm Dia)							
18	M/s Paragon Power cable Ltd., Plot No: 60, Phase -1, HSIIDC Industrial Estate, Kundli, Sonipat, Haryana - 131028 Contact No: 91-9910040000 & 991005711	1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average ±5% and resistivity 14Ohms/Kms (Max) as per IS-3975					
		240 sqmm, 3.5 Core (30 GI Strips - 4.0x0.8mm)	30.12.2025	GM(QS&S)/AE/BC-11/21-22/CYS-145 dtd: 31.12.2021 (Subject to first revalidation dated			

	91-9810049100 & 9811025711 E-mail: sales@paragoncables.com	16 sqmm, 4 Core (11 GI Strips - 4.0x0.8mm)		(subject to revalidation once before 30.12.2022 and then it will be revalidated once in 2 years)	
19	M/s Tirupati Plastomatics Pvt Ltd., B-141A, Road No.9-D, V.K.I. Area, Jaipur - 302013, Rajasthan Ph No: 911412331030, 9060906069, 9351507656 E-mail:contact@tirupatiplastomatics.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	28.07.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-39 dtd:28.07.2022	
20	M/s Insucon Cables & cond.(P)Ltd., #314-A, 3rd Floor, City centre, Sansar Chandra Road, Jaipur - 302001(Raj) & Factory Unit: No:5A, F-61-63, Bindayaka Industrial Area, Jaipur - 12. E-mail: marketing@insuconcables.com	1.1kV LT, XLPE, PVC extruded Inner Seath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 4C x 50 Sqmm, (17 GI Strips - 4.0 x 0.8mm) 4C x 16 Sqmm, (11 GI Strips - 4.0 x 0.8mm) 4C x 25 Sqmm (13 GI Strips - 4.0 x 0.8mm) 3.5C x 95 Sqmm, (21 GI Strips - 4.0 x 0.8mm) 3.5C x 150 Sqmm, (25GI Strips-4.0 x 0.8mm) 3.5C x 240Sqmm, (30 GI Strips - 4.0 x 0.8mm) 3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm) 3.5C x 400 Sqmm, (39 GI Strips - 4.0 x 0.8mm) 1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010 PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs PVC Wire - 16 Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs PVC Wire - 50 Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs PVC Wire - 95 Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs PVC Wire - 120 Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs PVC Wire - 150 Sqmm Al Wt: 41.4 Kg, Total Wt: 57 Kg/100 Mtrs PVC Wire - 185 Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs	22.07.2027 (subject to revalidation once in 2 years) 08.02.2023 08.02.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-41 dtd: 10.08.2022	
		11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia)	25.02.2027	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)	
		3C x 400 Sq mm, (51 GI Wires - 4mm Dia)	12.07.2024		
		1.1kV LT, XLPE, PVC extruded Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)	10.01.2024	GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	

21	M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 (E-mail:venkataraju.kt@havells.com)	4C x 16 sq mm (11 GI Strips - 4 x 0.8 mm)	07.04.2027	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)			
		4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)					
		3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)	31.01.2024	GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)			
		3.5C x 50 Sqmm, (16 GI Strips - 4 x 0.8 mm)	07.04.2024	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)			
		3.5C x 70 Sqmm, (18 GI Strips - 4 x 0.8 mm)					
		3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)	10.01.2024				
		3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	29.01.2024				
		3.5C x120 sq mm (23 GI Strips - 4.0 x 0.8mm)	07.04.2027				
		3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)	11.01.2024				
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	10.01.2024				
		3.5C x 300 Sqmm, (32 GI Strips - 4 x 0.8 mm)	07.04.2027				
		3.5C x 400 Sqmm, (39 GI Strips - 4 x 0.8 mm)					
22	M/s Apar Industries Limited, (Unit: Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 390007 (Factory Unit: Plot No: 158/163, GIDC, Umergaon Dist., Valsad, Gujarat - 396171) Contact No:91(080)23443932 /9986049678 E-mail:kr.sanjaya@apar.com	6.35/11kV HT XLPE UG Cable	30.07.2025			GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-140 dated:15.10.2020 (subject to revalidation every year)	
		3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable					
		11kV, 3 Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	28.03.2023			BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-65 dtd:28.09.2022 (subject to revalidation once in 2 years)	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)					
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)					
23	M/s Vardhman Cables & Conductors., 129/C, Shinoli(B.K),Taluk:Chandgad, Dist :Kolhapur, Maharashtra - 416507 Contact No: (02320) 236444/ 236482 E-mail: bharatcab@gmail.com	1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	03.09.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-72 dtd:18.10.2022			
		10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm)					
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)					
		95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)					
		120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)					
		185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)					
		240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)					
300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)							
24	M/s Dynamic Cables Ltd, Registered office: F-260, Road No.13, VKI Area, Jaipur-302013 Unit III- H-581A-592A, Road No:6, VKI Area, Jaipur- 302013 Contact No: 911412262589, 4042005 E-mail: info@dynamiccables.co.in	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	24.12.2026	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-74 dtd:19.10.2022(Subject to revalidation once in 2 years)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)					
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	23.01.2025				