

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto	
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(QS&S)/DGM-3/ BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021	
		3CX400sq.mm (51 GI Wires - 4mm Dia)				
		11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	31.12.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)				
		4 Core, 2.5 Sqmm, 21 No GI Wires (1.4mm)	29.06.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		4 Core, 6 Sqmm, 25 No GI Wires (1.6mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)				
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)				
		3.5C x 185Sq mm, (28 GI Strips - 4.0 x 0.8mm)				
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		3.5C x 150Sq mm, (25 GI Strips - 4.0 x 0.8mm)				
		3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)				
		3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)				
		4C x 10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)				
1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010						
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021			
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs						
11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)						
11kV 3C x 95 sq. mm. (54 GI Wires - 2.5mm dia)	31.08.2025	GM(Q,S&S)DGM -3/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)	20.12.2023 GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021			
11kV 3x240 sq. mm (55 GI Wires - 3.15mm dia)						
11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)						
3CX400sq.mm (51 GI Wires - 4mm Dia)	02.01.2023	GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021				
1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975						
6 Sqmm, 2Core,(24 GI wire - 1.4mm)						
10Sqmm, 2Core,(9GI Strips - 4.0 x 0.8mm)						

2	<p>M/s Polycab India Ltd., (Formerly Polycab Wires Limited) 74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore – 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com</p>	<p>10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm) 16 Sqmm, 2Core,(9 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)</p>	05.10.2022		<p>05.10.2022 GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dttd:20.12.2021</p>
3	<p>M/s Dynamic Cables Ltd., H-581-A-592-A, Road No:6. VKI Area, Jaipur - 302013</p>	<p>11kV, 3 x 95 sq. mm HT XLPE UG cable 11kV, 3 x 240 sq. mm HT XLPE UG cable 11kV, 3 x 400 sq. mm HT XLPE UG cable</p>	12.09.2022	<p>GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-163 dated:07.10.2017 (Subject revalidation every year)</p>	<p>GM(QS&S)/DGM(EI)-3/BC-11/20-21/CYS-163 dttd:09.11.2020</p>
4	<p>M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868/869, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085145, 7230085146 E-mail:bhiwadi@gemscab.com , pathredi@gemscab.com</p>	<p>11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires – 2.5mm Dia) 3CX240sq.mm (55 GI Wires – 3.15mm Dia) 3CX400sq.mm (51 GI Wires – 4mm Dia)</p>	05.07.2026	<p>GM(QS&S)/DGM-3/BC-11/21-22/CYS-32 dttd:05.07.2021 (Subject to revalidation once in 2 years)</p>	
5	<p>M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai – 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East – 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)</p>	<p>1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm)) 4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm)) 19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm)) 2 Core, 6 Sq mm, (24 No GI Wires (1.4mm)) 4 Core, 16 Sq mm, (30 No GI Wires (1.6mm)) 1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 2C x 6 Sq mm,(24 GI wire - 1.4mm) 4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm) 3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm) 3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)</p>	22.04.2024	<p>GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)</p>	<p>16.08.2023 GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dttd:16.08.2021 16.08.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dttd:16.08.2021</p>
6	<p>M/s Torrent Cables Limited, Yoginagar, Mission Road, Nadiad - 387002 Changed the Company name to :M/s Torrent Power Limited, Yoginagar, Mission Road, Nadiad - 387002 . Gujarat</p>	<p>11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX240sq.mm (55 GI Wires - 3.15mm Dia)</p>	05.10.2022	<p>GM(QS&S)/DGM-3/BC-11/19-20/cys-163 dated:07.10.2017 (Subject revalidation every year)</p>	<p>05.10.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dttd:21.01.2021</p>

		3CX400sq.mm (51 GI Wires - 4mm Dia)	20.05.2024	20/CYS-116 dtd:18.09.2019	19.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021
7	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkatta-700091. Works unit 1: IDOCD centre, khursha-752054, Odisha Works unit 2: Nandanagar Industrial Estate, Kashipur-244713, Uttarakhand E-mail: info@guptapower.com/ rhino@guptapower.com Ph No:91-33-40657348	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 185Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 400Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)	28.04.2026 30.05.2023	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
8	M/s KEI Industries Ltd, Okhla industrial Area Phase-1, New Delhi Factory Unit: SP-919/920/922, RIICO Industrial Area, Ph.III, Bhiwadi Distt. Alwar-301019, Rajasthan. Tel No: 01493-220106/221731 & 080-23466260/23466255 Email: mumbai@kei-ind.com, bhiwadi@kei-ind.com & banglore@kei-ind.com	11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975 3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia) 3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia) 3x400sq mm (51 GI wires - 4mm Dia)	29.06.2025 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/20-21/CYS-56 dtd:03.07.2020	07.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021
		1.1kV LT, XLPE, PVC exutruded Inner Seath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 2C x 16 Sq mm (9 GI Strips - 4.0 x 0.8mm) 4C x 10 Sq mm (10 GI Strips - 4.0 x 0.8mm) 4C x 25 Sq mm (13 GI Strips - 4.0 x 0.8mm) 3.5C x 50 Sq mm (16 GI Strips - 4.0 x 0.8mm) 3.5C x 70 Sq mm (18 GI Strips - 4.0 x 0.8mm) 3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm) 3.5Cx 150 sq mm (25 GI Strips - 4.0 x 0.8mm) 3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm) 3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm) 3.5C x 300 Sq mm (32 GI Strips - 4.0 x 0.8mm) 3.5C x 400 Sq mm (39 GI Strips - 4.0 x 0.8mm)	24.11.2022	GM(QS&S)/DGM-3/AE/ BC-11/22-23/CYS-14 dtd:24.05.2022	
9	M/s Finolex Cables Limited, 26/27, Mumbai Pune Road, Pimpri, Pune-411 018	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia)	27.11.2023 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/19-20/CYS-188 dtd:01.01.2020	
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm) 16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)			

10	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase - II, IDA, Chelapally, Hyderabad - 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)			
		25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)					
		35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)					
		50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)					
		70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)					
		95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)					
		120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)					
		150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)					
		185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)					
		300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm)					
		400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)					
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)					
		10Core, 2.5 Sqmm, 28 No GI Wires (1.6mm)	13.12.2023				
11	M/s LKB Engineering Private Limited., Registered Office: 204&205, Shivam House, Karpura, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Distt. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average \pm 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975		GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)			
		300Sq mm, 3.5Core (32GI Strips - 4.0 x 0.8mm)	05.07.2024				
12	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi - 110040 Ph No:011-27318598, E-mail:info@primecabindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021		
		2C x 10 sqmm					
		4C x 10sq mm					
		4C x 16sq mm					
		4C x25sq mm					
		4C x 50sq mm					
		4C x 95sq mm					
		3.5C x 50sq mm					
		3.5C x 70 sq mm					
		3.5C x 95 sq mm					
		3.5C x 120 sq mm					
		3.5C x 150sq mm					
		3.5C x 240sq mm					
		1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires	30.11.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021		
		1C x 16 sqmm					
		1C x 25 sqmm					
		1C x 35 sqmm					
		1C x50 sqmm					
		1C x 70 sqmm					
		1C x 95 sqmm					
		1C x 120 sqmm					
		1C x 150 sqmm					
		1C x 185 sqmm					
		1C x 240 sqmm					
13	M/s Shanti Insulated Cable Co., C/o. Aриhant Cable Corporation, No:B-24/1, JHILMIL Industrial Area, Shahdara, Delhi - 110095 (Ph No:9311177331)	2C x 4sq mm to 3.5C x 400sq mm PVC Insulated and sheathed armour cable with Aluminium conductor	12.03.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-06 dated:13.04.2018 (Subject revalidation every year)	12.03.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-201 dated:23.12.2020		
		2Cx 0.5sq mm to 4C x 185sq mm PVC insulated and sheathed flexible cable of copper conductor					
14	M/s Keli Flex Cables, C/o. Aриhant Cable Corporation, No: A-34, 2nd Floor, Jhimil, Indl. Area, Shadara, Delhi - 110095.	1C x 0.5sq mm to 1C x 400sq mm PVC Insulated sheathed flexible cable with copper conductor	23.01.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-07 dated:13.04.2018 (Subject revalidation every year)	23.01.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-183 dated:09.12.2020		
		2C x 0.5sq mm to 24C x 0.5sq mm PVC Insulated Unsheathed flexible cable with copper conductor					
15	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 98 66 26 66 66	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	06.12.2025	GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-129 dated:07.12.2021			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)					
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)					
				3C x 400 Sqmm (51 GI Wires - 4mm Dia)			
				1.1kV LT, XLPE PVC exutrutred Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring stripthickness in average \pm 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975			
				10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm)			
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)					
		50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)					
		25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm)					

<p>191 40 29702652, 29702657 E-mail: info@spm-cables.in</p>	<p>70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm)</p> <p>95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)</p> <p>120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)</p> <p>150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm)</p> <p>185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)</p> <p>240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)</p> <p>300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)</p> <p>400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)</p>	<p>25.01.2026</p>	<p>GM(Q,S&S)DGM -3/ AE/BC-11/22-23/cys-12 dated:10.05.2022 (Subject to revalidation once in 2 years)</p>		
<p>16</p>	<p>M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080-26662172, 26860166)</p>	<p>1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010</p> <p>PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs</p> <p>PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs</p> <p>PVC Wire - 50Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs</p> <p>PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs</p> <p>PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs</p> <p>PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs</p> <p>PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs</p> <p>1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)</p> <p>2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)</p> <p>4Core, 2.5Sqmm, 21 No GI Wires (1.4mm)</p> <p>4Core, 6Sqmm, 25 No GI Wires (1.6mm)</p> <p>4 Core, 10Sqmm, 28 No GI Wires (1.6mm)</p> <p>19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)</p> <p>1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1,</p> <p>50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</p> <p>16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm)</p> <p>1.1kV LT, XLPE Copper/Aluminium UG cable IS-7098 Part - 1</p> <p>50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</p> <p>70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)</p> <p>95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)</p> <p>185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm)</p> <p>240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)</p> <p>400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)</p> <p>16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)</p>	<p>22.01.2026</p> <p>22.01.2026</p> <p>22.01.2026</p> <p>22.01.2026</p> <p>22.01.2026</p> <p>22.01.2026</p> <p>22.01.2026</p> <p>19.08.2024</p>	<p>GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021</p> <p>GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021</p> <p>GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021</p> <p>GM(Q,S&S)DGM -3/BC-11/19-20/cys-95 dated:23.08.2019</p> <p>GM(Q,S&S)DGM -3/BC-11/20-21/cys-193</p>	<p>19.12.2022</p>

		(54 GI Wires - 2.5mm Dia) (55 GI Wires - 3.15mm Dia) (51 GI Wires - 4mm Dia)		(subject to revalidation every year)	dated:21.12.2020
17	M/s Vikas Cable Company, No.13, Haiderpur Delhi - 110088 Contact No: 91-11-27495529 E-mail:info@vikascable.com	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as per IS - 3975 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm) 185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)	24.12.2027	GM(QS&S)/DGM(EI)-3/BC-11/21-22/CYS-167 dtd:21.02.2022 (Subject to first revalidation dated before 17.02.2023 and then it will be revalidated once in 2 years)	
18	M/s Gloster Cables Limited, Registered Office: No.183/184, (5-3-370 to 372A) 2nd Floor, Above Mody Motors, Rahtrapathi Road, Secunderabad-500003 Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 Ph No: 9180-22129305, 91-8454250511/12, 250769/71 Email-gclbanglore@glostercable.com, info@glostercable.com	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	20.08.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-127 dtd: 26.11.2021 (subject t to revalidation once in 2 years)	
19	M/s Paragon Power cable Ltd., Plot No: 60, Phase -1, HSIIDC Industrial Estate, Kundli, Sonipat, Haryana - 131028 Contact No: 91-9810049100 & 9811025711 E-mail: sales@paragoncables.com	1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average ±5% and resistivity 14Ohms/Kms (Max) as per IS-3975 240 sqmm, 3.5 Core (30 GI Strips - 4.0x0.8mm) 16 sqmm, 4 Core (11 GI Strips - 4.0x0.8mm)	30.12.2025	GM(QS&S)/AE/BC-11/21-22/CYS-145 dtd: 31.12.2021 (Subject to first revalidation dated before 30.12.2022 and then it will be revalidated once in 2 years)	
20	M/s Tirupati Plastomatics Pvt Ltd., B-141A, Road No.9-D, V.K.I. Area, Jaipur - 302013, Rajasthan Ph No: 911412331030, 9060906069, 9351507656 E-mail:contact@tirupatiplastomatics.com	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	28.07.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-39 dtd:28.07.2022	
	M/s Insucon Cables & cond.(P)Ltd., #314-A, 3rd Floor, City centre, Sansar Chandra Road, Jaipur - 302001(Rail)	1.1kV LT, XLPE, PVC exutrated Inner Seath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 4C x 50 Sqmm, (17 GI Strips - 4.0 x 0.8mm) 4C x 16 Sqmm, (11 GI Strips - 4.0 x 0.8mm) 4C x 25 Sqmm (13 GI Strips - 4.0 x 0.8mm) 3.5C x 95 Sqmm, (21 GI Strips - 4.0 x 0.8mm) 3.5C x 150 Sqmm, (25GI Strips-4.0 x 0.8mm) 3.5C x 240Sqmm, (30 GI Strips - 4.0 x 0.8mm) 3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm) 3.5C x 400 Sqmm, (39 GI Strips - 4.0 x 0.8mm)	22.07.2027 (subject to revalidation once in 2 years) 08.02.2023		

23	M/s Apar Industries Limited, (Unit: Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 390007 (Factory Unit: Plot No: 158/163, GIDC, Umergaon Dist., Valsad, Gujarat - 396171) Contact No:91(080)23443932 /9986049678 E-mail:kr.sanjaya@apar.com	3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable	30.07.2025	dated:15.10.2020 (subject to revalidation every year)	
		11kV, 3 Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	28.03.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-65 dtd:28.09.2022 (subject to revalidation once in 2 years)	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
3C x 400 Sq mm, (51 GI Wires - 4mm Dia)					