

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto	
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)		
		3CX400sq.mm (51 GI Wires - 4mm Dia)				
		HT XLPE UG cable	11kV, 3x95 sqmm HT XLPE UG cable	31.12.2021	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	31.12.2021 GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-223 dated: 19.01.2021
		Copper control cables 1.1kV class				
		1.1 kV 4x2.5sqmm Control cables	1.1 kV 4x6 sqmm Control cables	29.06.2021		29.06.2021 GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-223 dated: 19.01.2021
		1.1 kV 4x6 sqmm Control cables				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)	4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3)/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)				
		3.5C x 185Sq mm, (28 GI Strips - 4.0 x 0.8mm)				
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)				
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)	3.5C x 150Sq mm, (25 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	
		3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)				
		3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)				
		4C x 10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)				
		1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010				
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)				
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs						
2	M/s Universal Cables Limited, P.O. Birla, Vikas, Satna, Madhya Pradesh	11 kV, 3C X 95 sq.mm XLPE HT UG Cable	28.02.2021	GM(Q,S&S)DGM - 3)/BC-11/15-16/cys-13 dated:05.05.2016(subject to Revalidation)	Ravalidated upto 08.11.2020 vide cys-147dated: 08.11.2019	
	M/s Polycab India Ltd., (Formerly Polycab Wires Limited)	11kV 3C x 95 sq. mm. HT XLPE UG cable	31.08.2025	GM(Q,S&S)DGM - 3)/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)		
		11kV 3x240 sq. mm HT XLPE UG cable				
		11kV 3C x 400 sq. mm. HT XLPE UG cable	02.01.2022	GM(Q,S&S)DGM - 4)/BC-11/17-18/cys-274 dated:21.02.2018 (Subject revalidation every year)	29.10.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-154 dtd: 02.11.2020	
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		6 Sqmm, 2Core,(24 GI wire - 1.4mm)				
		10Sqmm, 2Core,(9GI Strips - 4.0 x 0.8mm)				
10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)						
16 Sqmm, 2Core,(9 GI Strips - 4.0 x 0.8mm)						

3	74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore – 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com	<table border="1"> <tr><td>16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)</td></tr> <tr><td>150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)</td></tr> <tr><td>185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)</td></tr> </table>	16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)	25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm)	25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)	25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)	35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)	35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm)	50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)	50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)	70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)	95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)	120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)	150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)	185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)	240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)	300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm)	400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)	05.10.2022		
16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)																					
25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm)																					
25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)																					
25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)																					
35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)																					
35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm)																					
50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)																					
50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)																					
70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)																					
95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)																					
120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)																					
150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)																					
185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)																					
240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)																					
300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm)																					
400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)																					
4	M/s Gloster Cables Limited, Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)- 502334 (Ph No: 91 8454250511/12, 250769/71) (E-mail:info@glostercable.com)	<table border="1"> <tr><td>11kV 3C x 240 sq.mm HT XLPE UG Cable</td></tr> <tr><td>11kV 3C x 400 sq.mm HT XLPE UG Cable</td></tr> <tr><td>11kV 3C x 95 sq.mm HT XLPE UG Cable</td></tr> </table>	11kV 3C x 240 sq.mm HT XLPE UG Cable	11kV 3C x 400 sq.mm HT XLPE UG Cable	11kV 3C x 95 sq.mm HT XLPE UG Cable	04.04.2022 20.06.2021	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-26 dated:12.05.2017 (Subject revalidation every year) GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-133 dated:16.09.2017 (Subject revalidation every year)	04.04.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-78 dtd:14.08.2020 20.06.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-78 dtd:14.08.2020													
11kV 3C x 240 sq.mm HT XLPE UG Cable																					
11kV 3C x 400 sq.mm HT XLPE UG Cable																					
11kV 3C x 95 sq.mm HT XLPE UG Cable																					
5	M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 (E-mail:venkataraju.kt@havells.com)	<table border="1"> <tr><td>11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)</td></tr> <tr><td>3CX95sq.mm (54 GI Wires - 2.5mm Dia)</td></tr> <tr><td>3CX240sq.mm (55 GI Wires - 3.15mm Dia)</td></tr> <tr><td>3C x 400 Sq mm, (51 GI Wires - 4mm Dia)</td></tr> <tr><td>1.1kV LT, XLPE, PVC exutrated Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975</td></tr> <tr><td>2C x 10 sq mm (9 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)</td></tr> <tr><td>3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)</td></tr> </table>	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	3CX95sq.mm (54 GI Wires - 2.5mm Dia)	3CX240sq.mm (55 GI Wires - 3.15mm Dia)	3C x 400 Sq mm, (51 GI Wires - 4mm Dia)	1.1kV LT, XLPE, PVC exutrated Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	2C x 10 sq mm (9 GI Strips - 4.0 x 0.8mm)	4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)	16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)	25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm)	3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)	4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)	3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)	3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)	3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	17.03.2022 23.01.2022 12.07.2024 20.12.2021 10.01.2024 20.12.2021 20.07.2022 31.01.2024 20.12.2021 10.01.2024 29.01.2024 11.01.2024 10.01.2024	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-28 dated:17.05.2017 (Subject revalidation every year) GM(Q,S&S)DGM - 3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021 17.03.2022 23.01.2022 09.02.2023 GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021 20.12.2021 09.02.2023 20.12.2021 20.07.2022 09.02.2023 21.12.2021 09.02.2023 09.02.2023 09.02.2023 09.02.2023	
11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)																					
3CX95sq.mm (54 GI Wires - 2.5mm Dia)																					
3CX240sq.mm (55 GI Wires - 3.15mm Dia)																					
3C x 400 Sq mm, (51 GI Wires - 4mm Dia)																					
1.1kV LT, XLPE, PVC exutrated Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975																					
2C x 10 sq mm (9 GI Strips - 4.0 x 0.8mm)																					
4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)																					
16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)																					
25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm)																					
3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)																					
4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)																					
3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)																					
3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)																					
3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)																					
3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)																					
		11kV, 3 x 95 sq. mm HT XLPE UG cable		GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-																	

6	M/s Dynamic Cables Ltd., H-581-A-592-A, Road No:6. VKI Area, Jaipur - 302013	11kV, 3 x 240 sq. mm HT XLPE UG cable 11kV, 3 x 400 sq. mm HT XLPE UG cable	12.09.2022	163 dated:07.10.2017 (Subject revalidation every year)	GM(QS&S)/DGM(EI)-3/BC-11/20-21/CYS-163 dtd:09.11.2020
7	M/s Insucon cables & Cond(P) Ltd., # 314-A, 3rd Floor, City centre, Sansar chandra Road, Jaipur-302001, Raj(Factory Unit: Road No:5A, F-61-63, Bindayaka Industrial Area, Jaipur-12)	Armoured LT UG Cable 1.1class	30.06.2022	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-72 dated:11.07.2017 (Subject revalidation every year)	30.06.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-169 dtd:12.11.2020
		4C x 16sq mm 3.5C x 95sq mm 3.5C x 240sq mm 3.5C x 400sq mm 4C x 25sq mm	30.06.2022		
8	M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868/869, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085145, 7230085146 E-mail:bhiwadi@gemscab.com , pathredi@gemscab.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	05.07.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-32 dtd:05.07.2021 (Subject to revalidation once in 2 years)	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)			
9	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai - 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East - 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.04.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)	
		2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm)) 4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm)) 19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm)) 2 Core, 6 Sq mm, (24 No GI Wires (1.4mm)) 4 Core, 16 Sq mm, (30 No GI Wires (1.6mm))			
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	22.04.2024		
		2C x 6 Sq mm,(24 GI wire - 1.4mm) 4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm) 3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm) 3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)			
10	M/s Torrent Cables Limited, Yognagar, Mission Road, Nadiad - 387002 Changed the Company name to :M/s Torrent Power Limited, Yognagar, Mission Road, Nadiad - 387002 , Gujarat	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	05.10.2022	GM(QS&S)/DGM-3/BC-11/19-20/CYS-116 dtd:18.09.2019	05.10.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021
		3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	20.05.2024		19.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021
	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkatta-700091. Works unit 1: IDOCD centre, khursha-752054, Odisha Works unit 2: Nandanagar Industrial	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)			

15	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase - II, IDA, Chelapally, Hyderabad - 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)			
		10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)					
		16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)					
		25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)					
		25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)					
		35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)					
		50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)					
		70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)					
		95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)					
		120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)					
		150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)					
		185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)					
		300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm)					
		400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)					
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)				13.12.2023	
10Core, 2.5 Sqmm, 28 No GI Wires (1.6mm)							
16	M/s Laser power & Infra Pvt Ltd, 4A, Pollock street, 3rd floor, Kolkata-700001 (Unit-1: Biprannapara, Jalan complex, P.S. Domjur, Hawrah-711411, Unit II: NH-6, Poly Park, Dhulagori, Howrah-711302)	11kV HT XLPE UG cable (Round & Flat Armour)					
		3C x 400sq mm	09.08.2022				
		3C x 240sq mm	22.11.2021				
		1.1kV LT XLPE UG Cable					
		3.5C x 240sq mm	14.09.2022	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	13.03.2021 GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-225 dated:13.03.2020		
		3.5C x 95sq mm	16.11.2021				
		4C x 16sq mm	14.09.2022				
		4C x 10sq mm					
		4C x 50sq mm					
		4C x 6sq mm					
4C x 25sq mm							
4C x 25sq mm							
17	M/s LKB Engineering Private Limited., Registered Office: 204&205, Shivam House, Karpuram, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Dist. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)	
		300Sq mm, 3.5Core (32GI Strips - 4.0 x 0.8mm)	05.07.2024				
18	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 40 29702652, 29702657 E-mail: info@spm-cables.in	6.35/11kV 3x95sq mm & 3x240sq mm HT XLPE UG cable	18.09.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-135 dated:08.10.2020 (Subject revalidation every year)			
19	M/s Apar Industries limited, (Unit Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 39000 (Factory Unit: Plot no: 158/163, GIDC, Umargaon Dist, Valsad, Gujarat - 396171) (Ph.No91(080)23443932/9986049678 email-kr.sanjay@apar.com	6.35/11kV HT XLPE UG Cable		GM(Q,S&S)DGM -3)/BC-11/20-21/cys-140 dated:15.10.2020 (subject to revalidation every year)			
		3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable	30.07.2025				
20	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi - 110040 Ph No:011-27318598, E-mail:info@primecableindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)			
		2C x 10 sqmm					
		4C x 10sq mm					
		4C x 16sq mm					
		4C x25sq mm					
		4C x 50sq mm					
		4C x 95sq mm					
		3.5C x 50sq mm					
		3.5C x 70 sq mm					
		3.5C x 95 sq mm					
		3.5C x 120 sq mm					
		3.5C x 150sq mm					
		3.5C x 240sq mm					
		1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires'				30.11.2025	
		1C x 16 sqmm					
		1C x 25 sqmm					
		1C x 35 sqmm					
		1C x50 sqmm					
		1C x 70 sqmm					
1C x 95 sqmm							
1C x 120 sqmm							
1C x 150 sqmm							
1C x 185 sqmm							
1C x 240 sqmm							
21	M/s Shanti Insulated Cable Co., C/o. Arihant Cable Corporation, No:B-24/1,	2C x 4sq mm to 3.5C x 400sq mm PVC Insulated and sheathed armour cable with Aluminium conductor	12.03.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-06 dated:13.02.2018	12.03.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-201		

25	M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080-26662172, 26860166)	PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
		PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs			
		PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs			
		PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs			
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
		2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)			
		4Core, 2.5Sqmm, 21 No GI Wires (1.4mm)			
		4Core, 6Sqmm, 25 No GI Wires (1.6mm)			
		4 Core, 10Sqmm, 28 No GI Wires (1.6mm)			
		19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
		1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1,			
		50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)			
		16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
		25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm)			
1.1kV LT, XLPE Copper/Aluminium UG cable IS-7098 Part - 1	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021			
50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)□					
70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)□					
95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)□					
185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm)□					
240Sqmm, 3.5 Core,(30 GI Strips - 4.0 x 0.8mm)□					
400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)□					
16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)□	19.08.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year)	19.12.2022 GM(Q,S&S)DGM - 3/BC-11/20-21/cys-193 dated:21.12.2020		
11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)					
(54 GI Wires - 2.5mm Dia)					
(51 GI Wires - 3.15mm Dia)					
(51 GI Wires - 4mm Dia)	12.05.2021	GM(QS&S)/DGM-3/BC-11/20-21/CYS-11 dtd:12.05.2020 (Subject to revalidation every year)			
11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975 • 95 Sqmm, (54 GI Wires - 2.5mm Dia) • 240 Sqmm, (55 GI Wires - 3.15mm Dia) • 400 Sqmm, (51 GI Wires - 4mm Dia)					
26	M/s Asian Galaxy Pvt Ltd, Plot No: 3& 4, 18 & 20A, Sector-IIDC, SIDCUL, Haridwar-249403 Ph No:01334-239638, 09953002912 Email: sales@v-marc.in	1.1kV LT, XLPE or Heat resistant PVC insulated, PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 • 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) • 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) • 400 Sqmm, 3.5 Core , (39 GI Strips - 4.0 x 0.8mm)	12.05.2021	GM(QS&S)/DGM-3/BC-11/20-21/CYS-11 dtd:12.05.2020 (Subject to revalidation every year)	
		1.1kV class HR (Heat Resistant) PVC Insulated & Sheathed Aluminium Single Core Wires as IS- 694:2010			
	M/s RR Kabel Limited, Survey No: 202/1, 202/2, 203	2.5sq mm			

27	& 327/3, P.O. Village Waghodia, khanda Road, Tal. Waghodia – 391760 Dist. Vadodara Contact No: 91-80-41250079/40902221 E-mail: bengaluru.rrkabel@rrglobal.com	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheath amoured UG LT cable as per IS-1551 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as pere IS - 3975 50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)	29.07.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-50 dtd:29.07.2021	
28	M/s Bonton Cables India Pvt Ltd Registered Office: Epitome Building No:05, 18th Floor, Tower –B, DLF Cyber City, Gurugram – 122001 (HR) Factory Unit: (Unit-II), A-6 (A), Kaharani Industrial area, Bhiwadi-301019 (Rajasthan) Contact No: 8130299032,8130299001, 8130299003	1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed amoured UG LT cable as per IS-1551 (Part -1) or IS – 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as pere IS - 3975 120Sq mm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 185Sq mm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240Sq mm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)	29.07.2022	GM(QS&S)/DGM-3/BC-11/21-22/CYS-51 dtd:29.07.2021	