

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	
		3CX400sq.mm (51 GI Wires - 4mm Dia)	17.02.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	
		HT XLPE UG cable	31.12.2021	GM(Q,S&S)DGM - 4/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	31.12.2021 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		11kV, 3x95 sqmm HT XLPE UG cable	31.12.2021	GM(Q,S&S)DGM - 4/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	31.12.2021 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		Copper control cables 1.1kV class	29.06.2021	GM(Q,S&S)DGM - 4/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	29.06.2021 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		1.1 kV 4x2.5sqmm Control cables	29.06.2021	GM(Q,S&S)DGM - 4/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	29.06.2021 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		1.1 kV 4x6 sqmm Control cables	29.06.2021	GM(Q,S&S)DGM - 4/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	29.06.2021 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 185Sq mm, (28 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 150Sq mm, (25 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		4C x 10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to Revalidation every year)	24.10.2023 GM(Q,S&S)DGM -3/BC-11/20-21 /cys-223 dated: 19.01.2021
		1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010			
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)			
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)			
2	M/s Universal Cables Limited, P.O. Birla, Vikas, Satna, Madhya Pradesh	11 kV, 3C X 95 sq.mm XLPE HT UG Cable	28.02.2021	GM(Q,S&S)DGM - 3/BC-11/15-16/cys-13 dated:05.05.2016(sub ject to Revalidation every year)	Ravalidated upto 08.11.2020 vide cys-147dated: 08.11.2019
	M/s Polycab India Ltd., (Formerly Polycab Wires Limited)	11kV 3C x 95 sq. mm. HT XLPE UG cable	31.08.2025	GM(Q,S&S)DGM - 3/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)	
		11kV 3x240 sq. mm HT XLPE UG cable	31.08.2025	GM(Q,S&S)DGM - 3/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)	
		11kV 3C x 400 sq. mm. HT XLPE UG cable	02.01.2022	GM(Q,S&S)DGM - 4/BC-11/17-18/cys-274 dated:21.02.2018 (Subject revalidation every year)	29.10.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-154 dtd: 02.11.2020
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		6 Sqmm, 2Core,(24 GI wire - 1.4mm)			
		10Sqmm, 2Core,(9GI Strips - 4.0 x 0.8mm)			
10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)					
16 Sqmm, 2Core,(9 GI Strips - 4.0 x 0.8mm)					

3	74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore – 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com	16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)	05.10.2022		
4	M/s Gloster Cables Limited, Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 (Ph No: 91 8454250511/12, 250769/71) (E-mail:info@glostercable.com)	11kV 3C x 240 sq.mm HT XLPE UG Cable 11kV 3C x 400 sq.mm HT XLPE UG Cable 11kV 3C x 95 sq.mm HT XLPE UG Cable	04.04.2022 20.06.2021	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-26 dated:12.05.2017 (Subject revalidation every year) GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-133 dated:16.09.2017 (Subject revalidation every year)	04.04.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-78 dtd:14.08.2020 20.06.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-78 dtd:14.08.2020
5	M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 (E-mail:venkataraju.kt@havells.com)	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3C x 400 Sq mm, (51 GI Wires - 4mm Dia) 1.1kV LT, XLPE, PVC exutrated Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 2C x 10 sq mm (9 GI Strips - 4.0 x 0.8mm) 4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm) 3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm) 4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm) 3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm) 3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm) 3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm) 3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	17.03.2022 23.01.2022 12.07.2024 20.12.2021 10.01.2024 20.12.2021 20.07.2022 31.01.2024 20.12.2021 10.01.2024 29.01.2024 11.01.2024 10.01.2024	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-28 dated:17.05.2017 (Subject revalidation every year) GM(Q,S&S)DGM - 3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021 17.03.2022 23.01.2022 09.02.2023 GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021 20.12.2021 09.02.2023 20.12.2021 20.07.2022 09.02.2023 21.12.2021 09.02.2023 09.02.2023 09.02.2023 09.02.2023
		11kV, 3 x 95 sq. mm HT XLPE UG cable		GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-	

6	M/s Dynamic Cables Ltd., H-581-A-592-A, Road No:6. VKI Area, Jaipur - 302013	11kV, 3 x 240 sq. mm HT XLPE UG cable	12.09.2022	163 dated:07.10.2017 (Subject revalidation every year)	GM(QS&S)/DGM(EI)-3/BC-11/20-21/CYS-163 dtd:09.11.2020
		11kV, 3 x 400 sq. mm HT XLPE UG cable			
7	M/s Insucon cables & Cond(P) Ltd., # 314-A, 3rd Floor, City centre, Sansar chandra Road, Jaipur-302001, Raj(Factory Unit: Road No:5A, F-61-63, Bindayaka Industrial Area, Jaipur-12)	Armoured LT UG Cable 1.1class	30.06.2022	GM(Q,S&S)DGM - 4)/BC-11/17-18 /cys-72 dated:11.07.2017 (Subject revalidation every year)	30.06.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-169 dtd:12.11.2020
		4C x 16sq mm			
		3.5C x 95sq mm			
		3.5C x 240sq mm			
		3.5C x 400sq mm			
		4C x 25sq mm	30.06.2022		
		PVC Insulatec & Unsheathed Aluminium Wires, Single Core Multistrand 1.1kV class			
		1C x 16 sqmm			
		1C x 50 sqmm			
		1C x 95 sqmm			
1C x120 sqmm					
1C x 150 sqmm					
1C x 185 sqmm					
1C x 240 sqmm					
8	M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085142, 7230085143 E-mail:bhiwadi@gemscab.com	11kV 3C x 95 sq.mm HT XLPE UG Cable	12.05.2021	GM(Q,S&S)DGM - 3)/BC-11/18-19/cys-159 dated:15.07.2016 (Subject revalidation every year)	12.05.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-42 dtd:18.06.2020
		11kV 3C x 240 sq.mm HT XLPE UG Cable	10.05.2021		
		11kV 3CX400sq.mm, HT XLPE UG cable	18.01.2024		
9	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai - 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East - 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.04.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)	
		2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm))			
		4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm))			
		19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm))			
		2 Core, 6 Sq mm, (24 No GI Wires (1.4mm))			
		4 Core, 16 Sq mm, (30 No GI Wires (1.6mm))	22.04.2024		
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average \pm 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		2C x 6 Sq mm,(24 GI wire - 1.4mm)			
		4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm)			
		3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm)			
3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)					
10	M/s Torrent Cables Limited, Yognagar, Mission Road, Nadiad - 387002 Changed the Company name to :M/s Torrent Power Limited, Yognagar, Mission Road, Nadiad - 387002 , Gujarat	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	05.10.2022	GM(QS&S)/DGM-3/BC-11/19-20/CYS-116 dtd:18.09.2019	05.10.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3CX400sq.mm (51 GI Wires - 4mm Dia)	20.05.2024		19.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021
11	M/s Gupta Power Infrastructure Ltd, EN 62, sector V, 7th Floor, Salt Lake City, kolkatta - 700091. (E-mail: infor@guptapower.com, rhino@guptapower.com)	HT XLPE UG Cable		GM(QS&S)/DGM-3/BC-11/17-18/CYS-90 dtd:05.08.2017	13.12.2020 GM(QS&S)/DGM-3/BC-11/19-20/CYS-169 dtd:16.12.2019
		3x95sq mm	12.04.2022		
		3x240sq mm	10.04.2022		
		3x400sq mm	18.04.2022		
		LT XLPE UG Cable			
		3.5x400sq mm XLPE LT UG cable,	15.06.2021		
		3.5x240sq mm XLPE LT UG cable,	15.06.2021		
		3.5x185sq mm, XLPE LT UG cable,	19.07.2021		
		3.5x95sq mm, XLPE LT UG cable	15.06.2021		
		4x16sq mm, XLPE LT UG cable	19.07.2021		
4x10sq mm, XLPE LT UG cable	19.07.2021				

12	M/s KEI Industries Ltd, Okhla industrial Area Phase-1, New Delhi Factory Unit: SP-919/920/922, RIICI Industrial Area, Ph:III, Bhiwadi Distt. Alwar-3010109	Armoured XLPE insulated LT UG Cable 1.1kV Class			GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021
		10 Sqmm, 4 Core	29.12.2021		29.12.2021
		16 Sqmm, 2 Core	17.08.2022		17.08.2022
		16 Sqmm, 4 Core	28.12.2021		28.12.2021
		25 Sqmm, 4 Core	03.01.2022		03.01.2022
		35 Sqmm, 3.5 Core	17.08.2022	GM(QS&S)/DGM-3/BC-11/17-18/CYS-137 dtd:20.09.2017	17.08.2022
		50 Sqmm, 3.5 Core			
		70 Sqmm, 3.5 Core			
		95 Sqmm, 3.5 Core			
		150 Sqmm, 3.5 Core			
		185 Sqmm, 3.5 Core			
		240 Sqmm, 3.5 Core			
300 Sqmm, 3.5 Core	22.06.2022		22.06.2022		
400 Sqmm, 3.5 Core	18.07.2022		18.07.2022		
11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975					
3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia)	29.06.2025 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/20-21/CYS-56 dtd:03.07.2020	07.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021		
3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia)					
3x400sq mm (51 GI wires - 4mm Dia)	10.07.2022		10.07.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021		
13	M/s Finolex Cables Limited, 26/27, Mumbai Pune Road, Pimpri, Pune-411 018	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	27.11.2023 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/19-20/CYS-188 dtd:01.01.2020	
14	M/s KEC International Limited(Cables Division), Survey No:803, Village: Godampura Taluka – Salvi Dist, Vadodara – 391520.	11kV, 3 Core, HTUG Cable fwith pressure extruded, inner sheeth ROUND WIRE ARMoured as per IS-7098 (Part-2)			
		3Cx95 Sqmm, (54 GI Wires - 2.5mm Dia)	03.01.2022	GM(QS&S)/DGM-4/BC-11/18-19/CYS-27 dtd:28.05.2017	03.01.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-218 dtd:11.01.2021
		3Cx240 Sqmm, (55 GI Wires - 3.15mm Dia)			
		11kV 3 x 400 sq.mm(51 GI Wires - 4mm Dia)			
		1.1kV 4 x 240 sq.mm XLPE, LT UG Cable 1.1kV class	28.03.2021		28.03.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-218 dtd:11.01.2021
		16 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (11 GI Strips - 4.0 x 0.8mm)	08.01.2022	GM(QS&S)/DGM-3/BC-11/20-21CYS-217 dtd:11.01.2021	
		25 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (12 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (13 GI Strips - 4.0 x 0.8mm)			
		50 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (16 GI Strips - 4.0 x 0.8mm)			
		50 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (17 GI Strips - 4.0 x 0.8mm)			
95 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (21 GI Strips - 4.0 x 0.8mm)					
240 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (30 GI Strips - 4.0 x 0.8mm)					
15	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase – II, IDA, Chelapally, Hyderabad – 500051. Ph No: 8374098833.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
	10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)	21.11.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation		
	16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)				
	25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)				
	25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)				
	35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)				
	50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)				
	70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)				

	E-mail: smbasha@facables.com	95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)		every year	
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	13.12.2023		
16	M/s Laser power & Infra Pvt Ltd, 4A, Pollock street, 3rd floor, Kolkata-700001 (Unit-I: Biprannapara, Jalan complex, P.S. Domjur, Hawrah-711411, Unit II: NH-6, Poly Park, Dhulagori, Howrah-711302)	11kV HT XLPE UG cable (Round & Flat Armour) 3C x 400sq mm 3C x 240sq mm 1.1kV LT XLPE UG Cable 3.5C x 240sq mm 3.5C x 95sq mm 4C x 16sq mm 4C x 10sq mm 4C x 50sq mm 4C x 6sq mm 4C x 25sq mm	09.08.2022 22.11.2021 14.09.2022 16.11.2021 14.09.2022	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	13.03.2021 GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-225 dated:13.03.2020
17	M/s LKB Engineering Private Limited., Registered Office: 204&205, Shivam House, Karpura, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Distt. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	05.07.2024	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)	
18	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad – 500076 (Factory Unit: Sy.No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 40 29702652, 29702657 E-mail: info@spmables.in	6.35/11kV 3x95sq mm & 3x240sq mm HT XLPE UG cable	18.09.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-135 dated:08.10.2020 (Subject revalidation every year)	
19	M/s Apar Industries limited, (Unit Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 39000 (Factory Unit: Plot no: 158/163, GIDC, Umergaon Dist, Valsad, Gujarat - 396171) (Ph.No91(080)23443932/9986049678 email-kr.sanjay@apar.com	6.35/11kV HT XLPE UG Cable 3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable	30.07.2025	GM(Q,S&S)DGM -3)/BC-11/20-21/cys-140 dated:15.10.2020 (subject to revalidation every year)	
20	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi – 110040 Ph No:011-27318598, E-mail:info@primecabindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable 2C x 10 sqmm 4C x 10sq mm 4C x 16sq mm 4C x25sq mm 4C x 50sq mm 4C x 95sq mm 3.5C x 50sq mm 3.5C x 70 sq mm 3.5C x 95 sq mm 3.5C x 120 sq mm 3.5C x 150sq mm 3.5C x 240sq mm 1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires' 1C x 16 sqmm 1C x 25 sqmm 1C x 35 sqmm 1C x50 sqmm 1C x 70 sqmm 1C x 95 sqmm 1C x 120 sqmm 1C x 150 sqmm 1C x 185 sqmm 1C x 240 sqmm	11.06.2025 30.11.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	
21	M/s Shanti Insulated Cable Co., C/o. Arihant Cable Corporation, No:B-24/1, JHILMIL Industrial Area, Shahdara, Delhi - 110095 (Ph No:9311177331)	2C x 4sq mm to 3.5C x 400sq mm PVC Insulated and sheathed armour cable with Aluminium conductor 2Cx 0.5sq mm to 4C x 185sq mm PVC insulated and sheathed flexible cable of copper conductor	12.03.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-06 dated:13.04.2018 (Subject revalidation every year)	12.03.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-201 dated:23.12.2020
22	M/s Keli Flex Cables, C/o. Arihant Cable Corporation, No: A-34, 2nd Floor, Jhimil, Indl. Area, Shadara, Delhi – 110095.	1C x 0.5sq mm to 1C x 400sq mm PVC Insulated sheathed flexible cable with copper conductor 2C x 0.5sq mm to 24C x 0.5sq mm PVC Insulated Unsheathed flexible cable with copper conductor	23.01.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-07 dated:13.04.2018 (Subject revalidation every year)	23.01.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-183 dated:09.12.2020

23	<p>M/s SPM Power & Telecom Pvt Ltd., Regd Office: Plot No: A-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit 1: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yeldurthy Mandal-502255, Medan Factory Unit 2: Plot No: 136/2, phase II, I.D.A., Cherlapally, Hyderabad - 500051) Contact No: 91 40 29702652, 29702657 E-mail: info@spmables.in</p>	<p>11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)</p> <p>3CX95sq.mm (54 GI Wires - 2.5mm Dia)</p> <p>3CX240sq.mm (55 GI Wires - 3.15mm Dia)</p> <p>3C x 400 Sqmm (51 GI Wires - 4mm Dia)</p>	10.12.2021	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-186 dated:14.12.2020	
24	<p>M/s Vardhman Cables & Conductors., 129/C, Shinoli(B.K), Taluk:Chandgad, Dist :Kolhapur, Maharashtra - 416507 Contact No: (02320) 236444/ 236482 E-mail: bharatcab@gmail.com</p>	<p>1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975</p> <p>10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm)</p> <p>16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)</p> <p>120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)</p> <p>185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)</p> <p>240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)</p> <p>300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)</p>	29.12.2021	GM(Q,S&S)DGM(EL.)-3) /BC-11/ 20-21/Cys- 205 dated:29.12.2020	
25	<p>M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080- 26662172, 26860166)</p>	<p>1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010</p> <p>PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs</p> <p>PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs</p> <p>PVC Wire - 50Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs</p> <p>PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs</p> <p>PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs</p> <p>PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs</p> <p>PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs</p> <p>1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part- 1)</p> <p>2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)</p> <p>4Core, 2.5Sqmm, 21 No GI Wires (1.4mm)</p> <p>4Core, 6Sqmm, 25 No GI Wires (1.6mm)</p> <p>4 Core, 10Sqmm, 28 No GI Wires (1.6mm)</p> <p>19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)</p> <p>1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1,</p> <p>50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</p> <p>16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm)</p> <p>1.1kV LT, XLPE Copper/Aluminium UG cable IS- 7098 Part - 1</p> <p>50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</p> <p>70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)</p> <p>95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)</p> <p>185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm)</p>	22.01.2026	GM(QS&S)/DGM- 3/BC-11/20-21/CYS- 229 dtd:22.01.2021	

	240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)		
	400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)		
	16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)		
	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	19.08.2024	GM(Q,S&S)DGM - 3)/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year)
	(54 GI Wires - 2.5mm Dia)		
	(55 GI Wires - 3.15mm Dia)		
	(51 GI Wires - 4mm Dia)		
			19.12.2022 GM(Q,S&S)DGM -3)/BC-11/20-21/cys-193 dated:21.12.2020