

HT , LT U.G. cables & PVC insulated AI wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto	
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujarat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	1.1kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(Q,S&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)		
		3CX400sq.mm (51 GI Wires - 4mm Dia)				
		HT XLPE UG cable 11kV, 3x95 sqmm HT XLPE UG cable	31.12.2021	GM(Q,S&S)/DGM-4/BC-11/17-18 /cys-39 dated:19.05.2017 (Subject revalidation every year)	31.12.2021 GM(Q,S&S)/DGM-3/BC-	
		Copper control cables 1.1kV class 1.1 kV 4x2.5sqmm Control cables	29.06.2021			29.06.2021 GM(Q,S&S)/DGM-3/BC-
		1.1 kV 4x6 sqmm Control cables				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)	24.10.2024			24.10.2023 GM(Q,S&S)/DGM-3/BC-11/20-21 /cys-223 dated: 19.01.2021
		4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)				
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)				
		3.5C x 185Sq mm,(28 GI Strips - 4.0 x 0.8mm)				
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)				
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)	24.10.2024			24.10.2023 GM(Q,S&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)
		3.5C x 150Sq mm,(25 GI Strips - 4.0 x 0.8mm)				
		3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)				
		3.5C x 300 Sqmm,(32 GI Strips - 4.0 x 0.8mm)				
		4C x 10 Sqmm,(10 GI Strips - 4.0 x 0.8mm)				
1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010	18.01.2025			GM(Q,S&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)		
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs						
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs						
2	M/s Universal Cables Limited, P.O. Birla, Vikas, Satna, Madhya Pradesh	11 kV, 3C X 95 sq.mm XLPE HT UG Cable	28.02.2021	GM(Q,S&S)/DGM-3/BC-11/15-16/cys-13 dated:05.05.2016(subj ect to Revalidation every year)	Ravalidated upto 08.11.2020 vide cys-147dated: 08.11.2019	
3	M/s Polycab India Ltd., (Formerly Polycab Wires Limited) 74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore – 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com	11kV 3C x 95 sq. mm. HT XLPE UG cable	31.08.2025	GM(Q,S&S)/DGM-3/BC-11/20-21/CYS-		
		11kV 3x240 sq. mm HT XLPE UG cable				
		11kV 3C x 400 sq. mm. HT XLPE UG cable	02.01.2022	GM(Q,S&S)/DGM-4/BC-11/17-18/cys-274 dated:21.02.2018 (Subject revalidation every year)	29.10.2021 GM(Q,S&S)/DGM-3/BC-11/20-21/CYS-154 dtd: 02.11.2020	
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	05.10.2022			
		6 Sqmm, 2Core,(24 GI wire - 1.4mm)				
		10Sqmm, 2Core,(9GI Strips - 4.0 x 0.8mm)				
		10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)				
		16 Sqmm, 2Core,(9 GI Strips - 4.0 x 0.8mm)				
		16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)				
		25 Sqmm, 2 Core,(12 GI Strips - 4.0 x 0.8mm)				
25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)						
25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)						
35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)						
35 Sqmm, 4 Core,(15 GI Strips - 4.0 x 0.8mm)						
50 Sqmm,3.5 Core,(16 GI Strips - 4.0 x 0.8mm)						
50 Sqmm, 4 Core,(17 GI Strips - 4.0 x 0.8mm)						
70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)						
95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)						
120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)						
150 Sqmm, 3.5 Core,(25 GI Strips-4.0 x 0.8mm)						
185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)						
240Sqmm, 3.5 Core,(30 GI Strips - 4.0 x 0.8mm)						
300 Sqmm, 3.5 Core,(32 GI Strips - 4.0 x 0.8mm)						
400 Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)						
4	M/s Gloster Cables Limited, Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 (Ph No: 91 8454250511/12, 250769/71) (E-mail:info@glostercable.com)	11kV 3C x 240 sq.mm HT XLPE UG Cable	04.04.2022	GM(Q,S&S)/DGM-4/BC-11/17-18 /cys-	04.04.2021 GM(Q,S&S)/DGM-3/BC-	
11kV 3C x 400 sq.mm HT XLPE UG Cable	20.06.2021		GM(Q,S&S)/DGM-4/BC-11/17-18 /cys-133 dated:16.09.2017 (Subject revalidation every year)	20.06.2021 GM(Q,S&S)/DGM-3/BC-11/20-21/CYS-78 dtd:14.08.2020		
11kV 3C x 95 sq.mm HT XLPE UG Cable						

5	M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 (E-mail:venkataraju.kt@havells.com)	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	17.03.2022	GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-28 dated:17.05.2017 (Subject revalidation every year)	17.03.2022	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	23.01.2022		23.01.2022	
		3C x 400 Sq mm, (51 GI Wires - 4mm Dia)	12.07.2024		09.02.2023	
		1.1kV LT, XLPE, PVC extruded Inner Sheath Armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	GM(Q,S&S)DGM -3)/BC-11/20-21 /cys-255 dated:24.02.2021
		2C x 10 sq mm (9 GI Strips - 4.0 x 0.8mm)	20.12.2021	20.12.2021		
		4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)	10.01.2024	09.02.2023		
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)	20.12.2021	20.12.2021		
		25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm)	20.07.2022	20.07.2022		
		3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)	31.01.2024	09.02.2023		
		4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)	20.12.2021	21.12.2021		
		3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)	10.01.2024	09.02.2023		
		3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	29.01.2024	09.02.2023		
		3.5C x 185 sq mm (28 GI Strips - 4.0 x 0.8mm)	11.01.2024	09.02.2023		
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	10.01.2024	09.02.2023		
6	M/s Dynamic Cables Ltd., H-581-A-592-A, Road No:6. VKI Area, Jaipur - 302013	11kV, 3 x 95 sq. mm HT XLPE UG cable 11kV, 3 x 240 sq. mm HT XLPE UG cable 11kV, 3 x 400 sq. mm HT XLPE UG cable	12.09.2022	GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-163 dated:07.10.2017	GM(QS&S)/DGM(EI)-3/BC-11/20-21/CYS-163 dtd:09.11.2020	
7	M/s Insucon cables & Cond(P) Ltd., # 314-A, 3rd Floor, City centre, Sansar chandra Road, Jaipur-302001, Raj(Factory Unit: Road No:5A, F-61-63, Bindayaka Industrial Area, Jaipur-12)	Armoured LT UG Cable 1.1class 4C x 16sq mm 3.5C x 95sq mm 3.5C x 240sq mm 3.5C x 400sq mm 4C x 25sq mm PVC Insulatec & Unsheathed Aluminium Wires, Single Core Multistrand 1.1kV class 1C x 16 sqmm 1C x 50 sqmm 1C x 95 sqmm 1C x 120 sqmm 1C x 150 sqmm 1C x 185 sqmm 1C x 240 sqmm	30.06.2022 30.06.2022	GM(Q,S&S)DGM -4)/BC-11/17-18 /cys-72 dated:11.07.2017 (Subject revalidation every year)	30.06.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-169 dtd:12.11.2020	
8	M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085142, 7230085143 E-mail:bhiwadi@gemscab.com	11kV 3C x 95 sq.mm HT XLPE UG Cable 11kV 3C x 240 sq.mm HT XLPE UG Cable 11kV 3CX400sq.mm, HT XLPE UG cable	12.05.2021 10.05.2021 18.01.2024	GM(Q,S&S)DGM -3)/BC-11/18-19/cys-159 dated:15.07.2016 (Subject revalidation every year) GM(Q,S&S)DGM -3)/BC-11/18-19/cys-212 dated:12.03.2019 (Subject revalidation every year)	12.05.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-42 dtd:18.06.2020 16.06.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-42 dtd:18.06.2020	
9	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai - 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East - 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm)) 4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm)) 19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm)) 2 Core, 6 Sq mm, (24 No GI Wires (1.4mm)) 4 Core, 16 Sq mm, (30 No GI Wires (1.6mm)) 1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 2C x 6 Sq mm,(24 GI wire - 1.4mm) 4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm) 3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm) 3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)	22.04.2024 22.04.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)		

10	M/s Torrent Cables Limited, Yoginagar, Mission Road, Nadiad - 387002 Changed the Company name to :M/s Torrent Power Limited, Yoginagar, Mission Road, Nadiad - 387002 , Gujarat	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	05.10.2022 20.05.2024	GM(QS&S)/DGM-3/BC-11/19-20/CYS-116 dtd:18.09.2019	05.10.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021 19.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021
11	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkatta-700091. Works unit 1: IDOC centre, khursha 752054, Odisha Works unit 2: Nandanagar Industrial Estate, Kashipur-244713, Uttarakhand E-mail: info@guptapower.com/ rhino@guptapower.com Ph No:91-33-40657348	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia) 1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 185Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 400Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)	28.04.2026 28.04.2026 30.05.2023	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years) GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
12	M/s KEI Industries Ltd, Okhla industrial Area Phase-1, New Delhi Factory Unit: SP- 919/920/922, RIICI Industrial Area, Ph:III, Bhiwadi Distt. Alwar-3010109	Armoured XLPE insulated LT UG Cable 1.1kV Class 10 Sqmm, 4 Core 16 Sqmm, 2 Core 16 Sqmm, 4 Core 25 Sqmm, 4 Core 35 Sqmm, 3.5 Core 50 Sqmm, 3.5 Core 70 Sqmm, 3.5 Core 95 Sqmm, 3.5 Core 150 Sqmm, 3.5 Core 185 Sqmm, 3.5 Core 240 Sqmm, 3.5 Core 300 Sqmm, 3.5 Core 400 Sqmm, 3.5 Core 11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975 3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia) 3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia) 3x400sq mm (51 GI wires - 4mm Dia)	29.12.2021 17.08.2022 28.12.2021 03.01.2022 17.08.2022 22.06.2022 18.07.2022	GM(QS&S)/DGM-3/BC-11/17-18/CYS-137 dtd:20.09.2017 GM(QS&S)/DGM-3/BC-11/20-21/CYS-56 dtd:03.07.2020	GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021 29.12.2021 17.08.2022 28.12.2021 03.01.2022 17.08.2022 22.06.2022 18.07.2022
13	M/s Finolex Cables Limited, 26/27, Mumbai Pune Road, Pimpri, Pune-411 018	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia)	27.11.2023 (Subject to revalidation every year)	GM(QS&S)/DGM-3/BC-11/19-20/CYS-188 dtd:01.01.2020	07.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021 10.07.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-214 dtd:08.01.2021
14	M/s KEC International Limited(Cables Division), Survey No.803, Village: Godampura Taluka - Salvi Dist, Vadodara - 391520.	11kV, 3 Core, HTUG Cable fwith pressure extruded, inner sheeth ROUND WIRE ARMoured as per IS-7098 (Part-2) 3Cx95 Sqmm, (54 GI Wires - 2.5mm Dia) 3Cx240 Sqmm, (55 GI Wires - 3.15mm Dia) 11kV 3 x 400 sq.mm(51 GI Wires - 4mm Dia) 1.1kV 4 x 240 sq.mm XLPE, LT UG Cable 1.1kV class 16 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (13 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (16 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 4 Core, 1.1kV LT XLPE UG cable (17 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (21 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, 1.1kV LT XLPE UG cable (30 GI Strips - 4.0 x 0.8mm)	03.01.2022 28.03.2021 08.01.2022	GM(QS&S)/DGM-4/BC-11/18-19/CYS-27 dtd:28.05.2017 GM(QS&S)/DGM-3/BC-11/20-21/CYS-217 dtd:11.01.2021	03.01.2022 GM(QS&S)/DGM-3/BC-11/20-21/CYS-218 dtd:11.01.2021 28.03.2021 GM(QS&S)/DGM-3/BC-11/20-21/CYS-218 dtd:11.01.2021

15	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase – II, IDA, Chelapally, Hyderabad – 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	
		10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm) 16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)			
16	M/s Laser power & Infra Pvt Ltd, 4A, Pollock street, 3rd floor, Kolkata-700001 (Unit-1: Biprannapara, Jalan complex, P.S. Domjur, Hawrah-711411, Unit II: NH-6, Poly Park, Dhulagori, Howrah-711302)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	13.12.2023		
		10Core, 2.5 Sqmm, 28 No GI Wires (1.6mm)			
16		11kV HT XLPE UG cable (Round & Flat Armour)	09.08.2022	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	13.03.2021 GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-225 dated:13.03.2020
		3C x 400sq mm 3C x 240sq mm 1.1kV LT XLPE UG Cable 3.5C x 240sq mm 3.5C x 95sq mm 4C x 16sq mm 4C x 10sq mm 4C x 50sq mm 4C x 6sq mm 4C x 25sq mm	22.11.2021 14.09.2022 16.11.2021 14.09.2022		
17	M/s LKB Engineering Private Limited., Registered Office: 204&205, Shivam House, Karpura, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Distt. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	05.07.2024	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)	
18	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, LD.A., Nacharam, Hyderabad – 500076 (Factory Unit: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 40 29702652, 29702657 E-mail: info@spmables.in	6.35/11kV 3x95sq mm & 3x240sq mm HT XLPE UG cable	18.09.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-135 dated:08.10.2020 (Subject revalidation every year)	
19	M/s Apar Industries limited, (Unit Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road,	6.35/11kV HT XLPE UG Cable 3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable	30.07.2025	GM(Q,S&S)DGM -3)/BC-11/20-21/cys-140 dated:15.10.2020	
20	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi – 110040 Ph No:011-27318598, E-mail:info@primecableindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable 2C x 10 sqmm 4C x 10sq mm 4C x 16sq mm 4C x25sq mm 4C x 50sq mm 4C x 95sq mm 3.5C x 50sq mm 3.5C x 70 sq mm 3.5C x 95 sq mm 3.5C x 120 sq mm 3.5C x 150sq mm 3.5C x 240sq mm	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	
		1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires 1C x 16 sqmm 1C x 25 sqmm 1C x 35 sqmm 1C x50 sqmm 1C x 70 sqmm 1C x 95 sqmm 1C x 120 sqmm 1C x 150 sqmm 1C x 185 sqmm 1C x 240 sqmm	30.11.2025		
21	M/s Shanti Insulated Cable Co., C/o. Arihant Cable Corporation, No:B-24/1, JHILMIL Industrial Area, Shahdara, Delhi 110095 (Ph No:9311177331)	2C x 4sq mm to 3.5C x 400sq mm PVC Insulated and sheathed armour cable with Aluminium conductor 2Cx 0.5sq mm to 4C x 185sq mm PVC insulated and sheathed flexible cable of copper conductor	12.03.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-06 dated:13.04.2018 (Subject revalidation every year)	12.03.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-201 dated:23.12.2020
22	M/s Keli Flex Cables, C/o. Arihant Cable Corporation, No: A-34, 2nd Floor, Jhimil, Indl. Area, Shadara, Delhi – 110095.	1C x 0.5sq mm to 1C x 400sq mm PVC Insulated sheathed flexible cable with copper conductor 2C x 0.5sq mm to 24C x 0.5sq mm PVC Insulated Unsheathed flexible cable with copper conductor	23.01.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-07 dated:13.04.2018 (Subject revalidation every year)	23.01.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-183 dated:09.12.2020

23	M/s SPM Power & Telecom Pvt Ltd., Regd Office: Plot No: A-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit 1: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yeldurthy Mandal-502255, Medan Factory Unit 2: Plot No: 136/2, phase II, I.D.A., Cherlapally, Hyderabad - 500051) Contact No: 91 40 29702652, 29702657 E-mail: info@spmables.in	1.1kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3C x 400 Sqmm (51 GI Wires - 4mm Dia) 1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm) 185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)	10.12.2021	GM(Q,S&S)DGM -3/ BC-11/20-21/cys-186 dated:14.12.2020	
24	M/s Vardhman Cables & Conductors., 129/C, Shinoli(B.K), Taluk:Chandgad, Dist :Kolhapur, Maharashtra - 416507 Contact No: (02320) 236444/ 236482 E-mail: bharatecab@gmail.com	1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 400 Sqmm, 3.5 Core , (39 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core , (32 GI Strips - 4.0 x 0.8mm)	29.12.2021	GM(QS&S)DGM(EL.)-3) /BC-11/20-21/Cys-205 dated:29.12.2020	
25	M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080- 26662172, 26860166)	1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010 PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs PVC Wire - 50Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs 1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2Core, 2.5Sqmm, 18 No GI Wires (1.4mm) 4Core, 2.5Sqmm, 21 No GI Wires (1.4mm) 4Core, 6Sqmm, 25 No GI Wires (1.6mm) 4 Core, 10Sqmm, 28 No GI Wires (1.6mm) 19Core, 2.5Sqmm, 36 No GI Wires (1.6mm) 1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS 1554 (Part-1) or IS-7098 Part-1, 50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm) 25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm) 1.1kV LT, XLPE Copper/Aluminium UG cable IS-7098 Part - 1 50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	

		<p>70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) □</p> <p>95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) □</p> <p>185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm) □</p> <p>240Sqmm, 3.5 Core,(30 GI Strips - 4.0 x 0.8mm) □</p> <p>400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm) □</p> <p>16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) □</p> <p>11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)</p> <p>3CX95sq.mm (54 GI Wires - 2.5mm Dia)</p> <p>3CX240sq.mm (55 GI Wires - 3.15mm Dia)</p> <p>3CX400sq.mm (51 GI Wires - 4mm Dia)</p>	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
		<p>11kV, 3 Core, HTUG Cable for insulations High quality clean XLPE compound shall be used (Free from microvoids, Moisture content, ambers and contaminations) with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) Armouring wires dia in average ± 2.5% and resistivity 14.0 Ohms/KM (Max) as per IS-3975</p> <ul style="list-style-type: none"> • 95 Sqmm, (54 GI Wires - 2.5mm Dia) • 240 Sqmm, (55 GI Wires - 3.15mm Dia) • 400 Sqmm, (51 GI Wires - 4mm Dia) 	19.08.2024	GM(Q,S&S)DGM - 3/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year)	19.12.2022 GM(Q,S&S)DGM -3/BC-11/20-21/cys-193 dated:21.12.2020
26	M/s Asian Galaxy Pvt Ltd, Plot No: 3& 4, 18 & 20A, Sector-IIIDC, SIDCUL, Haridwar-249403 Ph No:01334-239638, 09953002912 Email: sales@v-marc.in	<p>1.1kV LT, XLPE or Heat resistant PVC insulated, PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975</p> <ul style="list-style-type: none"> • 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) • 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) • 400 Sqmm, 3.5 Core , (39 GI Strips - 4.0 x 0.8mm) 	12.05.2021	GM(QS&S)/DGM-3/BC-11/20-21/CYS-11 dtd:12.05.2020 (Subject to revalidation every year)	