

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	17.02.2025	GM(QS&S)/DGM-3/AE/BC-11//23-24CYS-75 dtd: 30.08.2023	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)			
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3CX400sq.mm (51 GI Wires - 4mm Dia)	24.10.2024		
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		3.5C x 70Sqmm, (18 GI Strips - 4.0 x 0.8mm)			
		3.5C x 150Sqmm, (25 GI Strips - 4.0 x 0.8mm)			
		3.5C x 240Sqmm, (30 GI Strips - 4.0 x 0.8mm)			
		3.5C x300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)			
		4Cx10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)			
		4C x 16Sqmm, (11 GI Strips - 4.0 x 0.8mm)			
		4C x 25Sqmm, (13 GI Strips - 4.0 x 0.8mm)			
		3.5C x 95Sqmm, (21 GI Strips - 4.0 x 0.8mm)			
		3.5C x 185Sqmm, (28 GI Strips - 4.0 x 0.8mm)			
3.5C x 400Sqmm, (39 GI Strips - 4.0 x 0.8mm)					
1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010	18.01.2025				
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs					
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs					
2	M/s GEMSCAB INDUSTRIES LTD., SP-4-868/869, RIICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan-301707 Ph No: 7230085142, 7230085143, 7230085144 E-mail: bhiwadi@gemscab.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)	05.07.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-32 dtd:05.07.2021 (Subject to revalidation once in 2 years)	05.07.2026 BESCOM/GM(QS&S)/DGM-3/AE/BC-11/24-25/CYS-08 dtd:17.04.2024
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)			
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
3	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai - 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East - 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.04.2024	GM(Q,S&S)DGM -3/ BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)	16.08.2023 GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dtd:16.08.2021
		2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm))			
		4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm))			
		19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm))			
		2 Core, 6 Sq mm, (24 No GI Wires (1.4mm))			
		4 Core, 16 Sq mm, (30 No GI Wires (1.6mm))	22.04.2024		
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		2C x 6 Sq mm,(24 GI wire - 1.4mm)			
		4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm)			
		3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm)			
3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)					
4	M/s Torrent Cables Limited, Yognagar, Mission Road, Nadiad - 387002 Changed the Company name	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)			

	to :M/s Torrent Power Limited, Yoginagar, Mission Road, Nadiad - 387002 , Gujarat	3CX400sq.mm (51 GI Wires - 4mm Dia)	20.05.2024		19.01.2023 GM(QS&S)/DGM-3/BC- 11/20-21/CYS-227 dtd:21.01.2021
5	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkatta-700091. Works unit 1: IDOCD centre, khursha-752054, Odisha Works unit 2: Nandanagar Industrial Estate, Kashipur-244713, Uttarakhand E-mail: info@guptapower.com/ rhino@guptapower.com Ph No:91-33-40657348	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part- 2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3CX400sq.mm (51 GI Wires - 4mm Dia)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21- 22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 185Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21- 22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		11kV, 3 Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia)	29.06.2025	GM(QS&S)/DGM-3/BC-11/22- 23/CYS-82 dtd:24.04.2022 (Subject to revalidation once in 2 years)	
		3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia)			
		3x400sq mm (51 GI wires - 4mm Dia)	11.11.2027		
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 2C x 16 Sq mm (9 GI Strips - 4.0 x 0.8mm)	10.11.2027		
		4C x 10 Sq mm (10 GI Strips - 4.0 x 0.8mm)			
		4C x 16 Sqmm, (11 GI Strips - 4.0 x 0.8mm)	04.11.2027		
		4C x 25 Sq mm (13 GI Strips - 4.0 x 0.8mm)			
		3.5C x 50 Sq mm (16 GI Strips - 4.0 x 0.8mm)	21.11.2027	GM(QS&S)/DGM-3/BC-11/22- 23/CYS-82 dtd:24.04.2022 (Subject to revalidation once in 2 years)	
		3.5C x 70 Sq mm (18 GI Strips - 4.0 x 0.8mm)			
		3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)			
		3.5Cx 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	02.11.2027		
		3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)			
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	06.02.2025		
		3.5C x 300 Sq mm (32 GI Strips - 4.0 x 0.8mm)	03.11.2027		
		3.5C x 400 Sq mm (39 GI Strips - 4.0 x 0.8mm)			
		3.5C x 120 Sq mm, (23 GI Strips - 4.0 x 0.8mm)	13.02.2025	GM(Q,S&S)DGM -3)/ AE/BC- 11/23-24/cys-191 dated:14.02.2024	
7	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase - II, IDA, Chelapally, Hyderabad - 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975 10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm) 16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm) 400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19- 20/cys-205 dated:04.02.2020 (Subject revalidation every year)	21.11.2024 BESCOM/GM (QS&S)/DGM- 3/AE/BC-11/24-25/CYS-20 dtd:30.04.2024

8	M/s LKB Engineering Private Limited., Registered Office: 204&205, Shivam House, Karpura, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Distt. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975		GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)	Not revalidated
		300Sq mm, 3.5Core (32GI Strips - 4.0 x 0.8mm)	05.07.2024		
9	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.I.D.C. Industrial Area, Narela, Delhi - 110040 Ph No:011-27318598, E-mail:info@primecabindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable 2C x 10 sqmm 4C x 10sq mm 4C x 16sq mm 4C x25sq mm 4C x 50sq mm 4C x 95sq mm 3.5C x 50sq mm 3.5C x 70 sq mm 3.5C x 95 sq mm 3.5C x 120 sq mm 3.5C x 150sq mm 3.5C x 240sq mm 1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires 1C x 16 sqmm 1C x 25 sqmm 1C x 35 sqmm 1C x50 sqmm 1C x 70 sqmm 1C x 95 sqmm 1C x 120 sqmm 1C x 150 sqmm 1C x 185 sqmm 1C x 240 sqmm	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	02.02.2025 GM(Q,S&S)DGM -3)/ BC-11/23-24/cys-180 dated: 03.02.2024 02.05.2024 GM(Q,S&S)DGM -3)/ BC-11/23-24/cys-180 dated: 03.02.2024
10	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 40 29702652, 29702657 E-mail: info@spmables.in	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3C x 400 Sqmm (51 GI Wires - 4mm Dia) 1.1kV LT, XLPE PVC exutrated Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring stripthickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975 10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm) 185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm) 240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm) 400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)	06.12.2025	GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-129 dated:07.12.2021	06.12.2025 GM(Q,S&S)DGM -3)AE/BC-11/23-24/cys-159 dated:12.01.2024
		1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010 PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	13.01.2025		

11	M/s SBEE Cables (India), Ltd, No:29, J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080-26662172, 26860166)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)	24.01.2025	GM(QS&S)/DGM-3/AE/BC-11/23-24/CYS-111 dtd: 31.10.2023	
		19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)			
		1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average ±5% and resistivity 14Ohms/Kms (Max) as per IS-3975 6 Sqmm, 2Core, (24 GI wire - 1.4mm)	01.03.2027 Subject to revalidation once in 2 years from the date of issue of this OM		
		10Sqmm, 2Core, (9GI Strips - 4.0 x 0.8mm)			
		10Sqmm, 4Core, (10GI Strips- 4.0 x 0.8mm)			
		16 Sqmm, 2Core, (9 GI Strips - 4.0 x 0.8mm)			
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 2 Core, (12 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm)			
		35 Sqmm, 3.5Core, (14 GI Strips - 4.0 x 0.8mm)			
		35 Sqmm, 4Core, (15 GI Strips - 4.0 x 0.8mm)			
		50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)			
		50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)			
		70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm)			
		95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)			
		120 Sqmm, 3.5Core, (23 GI Strips- 4.0 x 0.8mm)			
		150 Sqmm, 3.5 Core, (25GI Strips-4.0 x 0.8mm)			
		185 Sqmm, 3.5Core, (28 GI Strips - 4.0 x 0.8mm)			
		240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)			
300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)					
400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)					
11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia)	19.08.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year)	19.08.2024 GM(Q,S&S)DGM -3)AE/BC-11/22-23/cys-137 dated: 09.03.2023		
3CX240sq.mm (55 GI Wires - 3.15mm Dia)					
3CX400sq.mm (51 GI Wires - 4mm Dia)					
1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as per IS - 3975 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)	24.12.2027	GM(QS&S)/DGM(EI)-3/BC-11/21-22/CYS-167 dtd:21.02.2022 (Subject to revalidation once in 2 years)	07.01.2025 BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-107 dtd:07.01.2023		
25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm)					
70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm)					
95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)					
120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)					

12	M/s Vikas Cable Company, No.13, Haiderpur Delhi - 110088 Contact No: 91-11-27495529 E-mail:info@vikascable.com	150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm)			
		185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)			
		240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)			
		1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average \pm 5% resistivity 14ohm/kms (Max) as per IS - 3975			
		50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)	07.12.2025	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-107 dtd:07.01.2023 (Subject to revalidation once in 2 years)	
		400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)			
		1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS-694: 2010			
13	M/s Gloster Cables Limited, Registered Office: No.183/184, (5-3-370 to 372A) 2nd Floor, Above Mody Motors, Rahtrapathi Road, Secunderabad-500003 Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 Ph No: 9180-22129305, 91-8454250511/12, 250769/71 Email-gclbanglore@glostercable.com, info@glostercable.com	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	20.08.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-127 dtd: 26.11.2021 (subject to revalidation once in 2 years)	10.01.2026 GM(Q,S&S)DGM -3)AE/BC-11/23-24/cys-162 dated:18.01.2024
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
3CX400sq.mm (51 GI Wires - 4mm Dia)					
14	M/s Paragon Power cable Ltd., Plot No: 60, Phase -1, HSIIDC Industrial Estate, Kundli, Sonipat, Haryana - 131028 Contact No: 91-9810049100 & 9811025711 E-mail: sales@paragoncables.com	1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average \pm5% and resistivity 14Ohms/Kms (Max) as per IS-3975			
		240 sqmm, 3.5 Core (30 GI Strips - 4.0x0.8mm)	30.12.2025	GM(QS&S)/AE/BC-11/21-22/CYS-145 dtd: 31.12.2021 (Subject to first revalidation dated before 30.12.2022 and then it will be revalidated once in 2 years)	30.12.2025 BESCOM/GM(QS&S)/DGM-3/AE/BC-11/23-24/CYS-42 dtd:26.06.2023
		16 sqmm, 4 Core (11 GI Strips - 4.0x0.8mm)			
		1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average \pm5% and resistivity 14Ohms/Kms (Max) as per IS-3975			
		10 Sqmm, 4 Core, (10 GI Strips - 4 x 0.8 mm)	01.08.2024	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-69 dtd: 03.08.2023	
		16 Sqmm, 4 Core, (11 GI Strips - 4 x 0.8 mm)			
		25 Sqmm, 4 Core, (13 GI Strips - 4 x 0.8 mm)			
		35 Sqmm, 3.5 Core, (14 GI Strips - 4 x 0.8 mm)			
		50 Sqmm, 3.5 Core, (16 GI Strips - 4 x 0.8 mm)			
		70 Sqmm, 3.5 Core, (18 GI Strips - 4 x 0.8 mm)			
		95 Sqmm, 3.5 Core, (21 GI Strips - 4 x 0.8 mm)			
		120 Sqmm, 3.5 Core, (23 GI Strips - 4 x 0.8 mm)			
		150 Sqmm, 3.5 Core, (25 GI Strips - 4 x 0.8 mm)			
		185 Sqmm, 3.5 Core, (28 GI Strips - 4 x 0.8 mm)			
300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)					
15	M/s Tirupati Plastomatics Pvt Ltd., B-141A, Road No.9-D, V.K.I. Area, Jaipur-302013, Rajasthan	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)		BESCOM/GM(QS&S)/DGM-	

	<p>Ph No: 911412331030, 9060906069, 9351507656 E-mail:contact@tirupatiplastomatics.com</p>	<p>3CX240sq.mm (55 GI Wires - 3.15mm Dia)</p> <p>3CX400sq.mm (51 GI Wires - 4mm Dia)</p>	<p>06.06.2027</p>	<p>BESCOM/GM(QS&S)/DGM-3/AE/BC-11/23-24/CYS-76 dtd:31.08.2023 (Subject to revalidation once in 2 years)</p>	
16	<p>M/s Insucon Cables & cond.(P)Ltd., #314-A, 3rd Floor, City centre, Sansar Chandra Road, Jaipur - 302001(Raj) & Factory Unit: No:5A, F-61-63, Bindayaka Industrial Area, Jaipur - 12. E-mail: marketing@insuconcables.com</p>	<p>1.1kV LT, XLPE, PVC extruded Inner Seath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975</p> <p>4C x 50 Sqmm, (17 GI Strips - 4.0 x 0.8mm)</p> <p>4C x 16 Sqmm, (11 GI Strips - 4.0 x 0.8mm)</p> <p>4C x 25 Sqmm (13 GI Strips - 4.0 x 0.8mm)</p> <p>3.5C x 95 Sqmm, (21 GI Strips - 4.0 x 0.8mm)</p> <p>3.5C x 150 Sqmm, (25GI Strips-4.0 x 0.8mm)</p> <p>3.5C x 240Sqmm, (30 GI Strips - 4.0 x 0.8mm)</p> <p>3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)</p> <p>3.5C x 400 Sqmm, (39 GI Strips - 4.0 x 0.8mm)</p> <p>1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010</p> <p>PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs</p> <p>PVC Wire - 16 Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs</p> <p>PVC Wire - 50 Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs</p> <p>PVC Wire - 95 Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs</p> <p>PVC Wire - 120 Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs</p> <p>PVC Wire - 150 Sqmm Al Wt: 41.4 Kg, Total Wt: 57 Kg/100 Mtrs</p> <p>PVC Wire - 185 Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs</p> <p>PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs</p>	<p>22.07.2027</p> <p>18.08.2027</p> <p>22.07.2027</p> <p>18.08.2027</p>	<p>BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-78 dtd: 08.11.2022 (subject to revalidation once in 2 years)</p>	
17	<p>M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 (E-mail:venkataraju.kt@havells.com)</p>	<p>11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)</p> <p>3CX95sq.mm (54 GI Wires - 2.5mm Dia)</p> <p>3CX240sq.mm (55 GI Wires - 3.15mm Dia)</p> <p>3C x 400 Sq mm, (51 GI Wires - 4mm Dia)</p> <p>1.1kV LT, XLPE, PVC extruded Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975</p> <p>4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)</p> <p>4C x 16 sq mm (11 GI Strips - 4 x 0.8 mm)</p> <p>4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)</p> <p>3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)</p> <p>3.5C x 50 Sqmm, (16 GI Strips - 4 x 0.8 mm)</p> <p>3.5C x 70 Sqmm, (18 GI Strips - 4 x 0.8 mm)</p> <p>3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)</p>	<p>25.02.2027</p> <p>12.07.2024</p> <p>10.01.2024</p> <p>07.04.2027</p> <p>31.01.2024</p> <p>07.04.2024</p> <p>10.01.2024</p>	<p>BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)</p> <p>GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)</p> <p>BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)</p> <p>GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)</p> <p>BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022</p>	

		3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	29.01.2024	dtd:12.09.2022 (subject to revalidation once in 2 years)	
		3.5C x120 sq mm (23 GI Strips - 4.0 x 0.8mm)	07.04.2027		
		3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)	11.01.2024		
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	10.01.2024		
		3.5C x 300 Sqmm, (32 GI Strips - 4 x 0.8 mm)	07.04.2027		BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)
		3.5C x 400 Sqmm, (39 GI Strips - 4 x 0.8 mm)			
18	M/s Dynamic Cables Ltd, Registered office: F-260, Road No.13, VKI Area, Jaipur-302013 Unit III- H-581A-592A, Road No:6, VKI Area, Jaipur- 302013 Contact No: 911412262589, 4042005 E-mail: info@dynamiccables.co.in	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	24.12.2026	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-74 dtd:19.10.2022(Subject to revalidation once in 2 years)	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3C x 400 Sqmm, (51 GI Wires - 4mm Dia)	23.01.2025		
19	M/s Apar Industries Limited, (Unit: Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 390007 Factory Unit: Plot No: 158/163, GIDC, Umergaon Dist., Valsad, Gujarat - 396171 Contact No:91(080)23443932 /9986049678 E-mail: kr.sanjaya@apar.com	11kV, 3Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	16.05.2028	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-33 dtd: 12.06.2023 (Subject to revalidation once in 2 years from the date of issue of this OM)	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3C x 400 Sq mm, (51 GI Wires - 4mm Dia)			
20	M/s Shanti Insulated Cable Co., C/o. Arihant Corporation for supply of Ashirvadcab make No: B-24/1, JHIMIL Industrial Area, Shahdara, Delhi-110095 Ph No: 9311177331	1.1 kV, XLPE or Heat resistant PVC insulated, PVC extruded Inner Seath Armoured LTUG Cable as per IS-1554 (Part1) or IS-7098 Part-1, Armouring strip thickness and resistivity as per IS-3975			
		6 Sqmm, 2 Core, (24 GI Wire - 1.4 mm)	23.03.2028	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-34 dtd: 14.06.2023 (Subject to revalidation once in 2 years from the date of issue of this OM)	
		10 Sqmm, 2 Core, (9 GI Strips - 4 x 0.8 mm)			
		10 Sqmm, 4 Core, (10 GI Strips - 4 x 0.8 mm)			
		16 Sqmm, 2 Core, (9 GI Strips - 4 x 0.8 mm)			
		16 Sqmm, 4 Core, (11 GI Strips - 4 x 0.8 mm)			
		25 Sqmm, 2 Core, (12 GI Strips - 4 x 0.8 mm)			
		25 Sqmm, 3.5 Core, (12 GI Strips - 4 x 0.8 mm)			
		25 Sqmm, 4 Core, (13 GI Strips - 4 x 0.8 mm)			
		35 Sqmm, 3.5 Core, (14 GI Strips - 4 x 0.8 mm)			
		35 Sqmm, 4 Core, (15 GI Strips - 4 x 0.8 mm)			
		50 Sqmm, 3.5 Core, (16 GI Strips - 4 x 0.8 mm)			
		50 Sqmm, 4 Core, (17 GI Strips - 4 x 0.8 mm)			
		70 Sqmm, 3.5 Core, (18 GI Strips - 4 x 0.8 mm)			
		95 Sqmm, 3.5 Core, (21 GI Strips - 4 x 0.8 mm)			
		120 Sqmm, 3.5 Core, (23 GI Strips - 4 x 0.8 mm)			
		150 Sqmm, 3.5 Core, (25 GI Strips - 4 x 0.8 mm)			
		185 Sqmm, 3.5 Core, (28 GI Strips - 4 x 0.8 mm)			
		240 Sqmm, 3.5 Core, (30 GI Strips - 4 x 0.8 mm)			
21	M/s Rotoplast Wires and Cables, Gala No: 3 & 4, Nr. Shri Ganesh Industrial Estate, Beside Green Masjid, Parmer Talao, Vasai Fata, Vasai (E), Dist. Palghar - 401208 Contact No: 9986672160	1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average ±5% and resistivity 140hms/Kms (Max) as per IS-3975			
		10 Sqmm, 4 Core, (10 GI Strips - 4 x 0.8 mm)	04.05.2028	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-71 dtd: 11.08.2023 (Subject to revalidation once in 2 years from the date of issue of this OM)	
		16 Sqmm, 4 Core, (11 GI Strips - 4 x 0.8 mm)			
		25 Sqmm, 4 Core, (13 GI Strips - 4 x 0.8 mm)			
		35 Sqmm, 3.5 Core, (14 GI Strips - 4 x 0.8 mm)			
		50 Sqmm, 3.5 Core, (16 GI Strips - 4 x 0.8 mm)			

	Email:rotoplastcables@gmail.com	70 Sqmm, 3.5 Core, (18 GI Strips - 4 x 0.8 mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4 x 0.8 mm) 120 Sqmm, 3.5 Core, (23 GI Strips - 4 x 0.8 mm) 150 Sqmm, 3.5 Core, (25 GI Strips - 4 x 0.8 mm) 1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1) 2 Core, 2.5 Sqmm, (18 No GI Wires (1.4mm)) 4 Core, 2.5 Sqmm, (21 No GI Wires (1.4mm)) 19 Core, 2.5 Sqmm, (36 No GI Wires (1.6mm))	02.05.2028	years from the date of issue of this OM)	
22	M/s Polycab India Ltd., (Formerly Polycab Wires Limited) Factory Unit: Village Nurpura, Plot No.67-69,71-72, 75-76, 102, 103, 104/1-2, 105,106, 116/2, Halol Vadodara Road, Halol, Tal Halol, Panchmahal, Gujarat - 389350 Contact No: 91 22 24327070-74 9606522802 E-mail: info@polycab.com/ vinay.somashekar@ polycab.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX400sq.mm (51 GI Wires - 4mm Dia) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1,Armouring strip thickness in average ± 5% and resistivity 14Ohms/Kms (Max) as per IS 3975 6 Sqmm, 2Core, (24 GI wire - 1.4mm) 10Sqmm, 2Core, (9GI Strips - 4.0 x 0.8mm) 10Sqmm,4Core, (10GI Strips- 4.0 x 0.8mm) 16 Sqmm, 2Core, (9 GI Strips - 4.0 x 0.8mm) 16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 2 Core, (12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 3.5 Core, (12 GI Strips - 4.0 x 0.8mm) 25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 3.5Core, (14 GI Strips - 4.0 x 0.8mm) 35 Sqmm, 4Core, (15 GI Strips - 4.0 x 0.8mm) 50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm) 50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm) 70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm) 95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm) 120 Sqmm, 3.5Core, (23 GI Strips-4.0 x 0.8mm) 150 Sqmm, 3.5 Core, (25GI Strips-4.0 x 0.8mm) 185 Sqmm, 3.5Core, (28 GI Strips - 4.0 x 0.8mm) 240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm) 300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm) 400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)	31.05.2024	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-156 dtd: 12.01.2024	
23	M/s Paramount Communications Limited, SP-30A, 30B & E-31, RIICO Industrial area, Khushkhera District, Alwar, Rajasthan-301707 Ph No: 91-11-45618800 E-mail: pcl@paramountcables.com	11kV, 3 Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2) 3CX95sq.mm (54 GI Wires - 2.5mm Dia) 3CX240sq.mm (55 GI Wires - 3.15mm Dia) 3C x 400 Sq mm, (51 GI Wires - 4mm Dia)	28.12.2025	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-169 dtd: 25.01.2024	