

HT , LT U.G. cables & PVC insulated Al wire

Sl.No	Name of the firm	particulars	Valid upto	O.M.No. & Date	Revalidated upto	
1	M/s. Chandresh Cables Ltd, G-6, New Madhavpura market, Near Police Commissioner Office, Ahmedabad-380004 Factory Unit: Block No.1108, Chhatral Taluka Kalol Dist, Gandhinagar - 382729 Gujrat (E-mail: sales@avocab.com, sangameshbc@avocab.com) (Ph No: 91-79-25623055, 25623056, 25623057)(Mob: 9901491011)	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	17.02.2025	GM(QS&S)/DGM-3/ BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021	
		3CX400sq.mm (51 GI Wires - 4mm Dia)				
		11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	31.12.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)				
		4 Core, 2.5 Sqmm, 21 No GI Wires (1.4mm)	29.06.2026	GM(QS&S)/DGM-3/BC-11/CYS-79 dtd:02.09.2021 (Subject to revalidation once in 2 years)		
		4 Core, 6 Sqmm, 25 No GI Wires (1.6mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		4C x 16Sq mm,(11 GI Strips - 4.0 x 0.8mm)				
		4C x 25Sq mm,(13 GI Strips - 4.0 x 0.8mm)				
		3.5C x 95Sq mm,(21 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(Q,S&S)DGM -3)/BC-11/19-20/Cys-182 dated:27.12.2019 (subject to revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021	
		3.5C x 185Sq mm, (28 GI Strips - 4.0 x 0.8mm)				
		3.5C x 400Sq mm,(39 GI Strips - 4.0 x 0.8mm)				
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured LT UG cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975				
		3.5C x 70Sq mm,(18 GI Strips - 4.0 x 0.8mm)				
3.5C x 150Sq mm, (25 GI Strips - 4.0 x 0.8mm)						
3.5C x 240Sq mm,(30 GI Strips - 4.0 x 0.8mm)	24.10.2024	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021			
3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)						
4C x 10 Sqmm, (10 GI Strips - 4.0 x 0.8mm)						
1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS- 694: 2010						
PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	18.01.2025	GM(QS&S)/DGM-3/BC-11/20-21/CYS-69 dtd:11.08.2020. (Subject revalidation every year)	02.09.2023 GM(Q,S&S)DGM -3)/BC-11/21-22 /Cys-79 dated: 02.09.2021			
PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs						
2	M/s Polycab India Ltd., (Formerly Polycab Wires Limited) 74/8-9, Daman Indl Estate Village, Kadalya, Daman and 67-72 Noorpura, Tal- Halol. B-78, No:18, 4th Main Road, KSSIDC Industrial Estate, 6th block, Rajajinagar, Bangalore - 560010. Contact No: 8017036678 E-mail: kumar.gaurav@polycab.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		11kV 3C x 95 sq. mm. (54 GI Wires - 2.5mm dia)	31.08.2025	GM(Q,S&S)DGM -3)/BC-11/20-21/CYS-153 dtd:02.11.2020 (Subject revalidation every year)	20.12.2023 GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021	
		11kV 3x240 sq. mm (55 GI Wires - 3.15mm dia)				
		11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
3CX400sq.mm (51 GI Wires - 4mm Dia)	02.01.2023	GM(Q,S&S)/AE/BC-11/21-22/CYS-138 dtd:20.12.2021				
3	M/s GEMSCAB INDUSTRIES LTD., No: 40, Rajasthani Udyog Nagar, G.T Karnal Road, Delhi-110 033 (Factory unit: SP-4-868/869, RICO Industrial area, Pathredi (Bhiwadi), P.O Tapukara, Dist, Alwar, Rajasthan) Contact No: 7230085145, 7230085146 E-mail:bhiwadi@gemscab.com ,	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMoured as per IS-7098 (Part-2)				
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)				
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	05.07.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-32 dtd:05.07.2021 (Subject to revalidation once in		

	pathredi@gemscab.com	3CX400sq.mm (51 GI Wires - 4mm Dia)		2 years)				
4	M/s Vishal cables Pvt Ltd., No:56, Gr. Floor, Ashoka Shopping Centre, G.T. Hospital Complex, L.T. Road, Mumbai - 400001 Factory Unit: Plot No: E-41, Addl. Ambernath MIDC, Anandnagar, Ambernath East - 421506, Thane, Maharashtra Contact No: 0251-2620077 (E-mail: vishalcables@gmail.com)	1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)	22.04.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)	16.08.2023 GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dtd:16.08.2021			
		2 Core, 2.5 Sq mm (18 No GI Wires (1.4mm))						
		4 Core, 2.5 Sq mm, (21 No GI Wires (1.4mm))	22.04.2024		GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dtd:16.08.2021			
		19 Core, 2.5 Sq mm, (36 No GI Wires (1.6mm))						
		2 Core, 6 Sq mm, (24 No GI Wires (1.4mm))	GM(QS&S)/DGM-3/BC-11/19-20/cys-64 dated:11.07.2019 (Subject revalidation every year)			16.08.2023 GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dtd:16.08.2021		
		4 Core, 16 Sq mm, (30 No GI Wires (1.6mm))						
		1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975					22.04.2024	GM(QS&S)/DGM-3/BC-11/21-22/CYS-67 dtd:16.08.2021
		2C x 6 Sq mm,(24 GI wire - 1.4mm)						
4C x 16 Sq mm, (11 GI Strips - 4.0 x 0.8mm)								
3.5C x 95 Sq mm, (21 GI Strips - 4.0 x 0.8mm)								
3.5C x 400 Sq mm, (39 GI Strips - 4.0 x 0.8mm)								
5	M/s Torrent Cables Limited, Yoginagar, Mission Road, Nadiad - 387002 Changed the Company name to :M/s Torrent Power Limited, Yoginagar, Mission Road, Nadiad - 387002 , Gujarat	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)						
		3CX400sq.mm (51 GI Wires - 4mm Dia)	20.05.2024		19.01.2023 GM(QS&S)/DGM-3/BC-11/20-21/CYS-227 dtd:21.01.2021			
6	M/s Gupta Power Infrastructure Ltd., Registered Office: EN-62, Sector V, 7th Floor, Salt Lake City, Kolkata-700091. Works unit 1: IDOCD centre, khursha 752054, Odisha Works unit 2: Nandanagar Industrial Estate, Kashipur-244713, Uttarakhnad E-mail: info@guptapower.com/ rhino@guptapower.com Ph No:91-33-40657348	11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	28.04.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)						
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)	28.04.2026			GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)		
		3CX400sq.mm (51 GI Wires - 4mm Dia)						
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975	30.05.2023				GM(QS&S)/DGM-3/BC-11/21-22/CYS-12 dtd:28.04.2021 (Subject to revalidation once in 2 years)	
		185Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)						
240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)								
400Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)								
7	M/s KEI Industries Ltd, Okhla industrial Area Phase-1, New Delhi Factory Unit: SP-919/920/922, RIICO Industrial Area, Ph.III, Bhiwadi Distt. Alwar-301019, Rajasthan. Tel No: 01493-220106/221731 & 080-23466260/23466255 Email: mumbai@kei-ind.com, bhiwadi@kei-ind.com & banglore@kei-ind.com	11kV, 3 Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	29.06.2025	GM(QS&S)/DGM-3/BC-11/22-23/CYS-82 dtd:24.04.2022 (Subject to revalidation once in 2 years)	GM(QS&S)/DGM-3/BC-11/22-23/CYS-82 dtd:24.04.2022			
		3 x 95 Sqmm, (54 GI Wires - 2.5mm Dia)						
		3 x 240 Sqmm, (55 GI Wires - 3.15mm Dia)	11.11.2027			GM(QS&S)/DGM-3/BC-11/22-23/CYS-82 dtd:24.04.2022 (Subject to revalidation once in 2 years)		
		3x400sq mm (51 GI wires - 4mm Dia)						
		1.1kV LT, XLPE, PVC exutruded Inner Seath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	10.11.2027				GM(QS&S)/DGM-3/BC-11/22-23/CYS-82 dtd:24.04.2022	
		2C x 16 Sq mm (9 GI Strips - 4.0 x 0.8mm)						
4C x 10 Sq mm (10 GI Strips - 4.0 x 0.8mm)	04.11.2027	GM(QS&S)/DGM-3/BC-11/22-23/CYS-82 dtd:24.04.2022						
4C x 16 Sqmm, (11 GI Strips - 4.0 x 0.8mm)								
4C x 25 Sq mm (13 GI Strips - 4.0 x 0.8mm)	21.11.2027		GM(QS&S)/DGM-3/BC-11/22-23/CYS-82 dtd:24.04.2022					
3.5C x 50 Sq mm (16 GI Strips - 4.0 x 0.8mm)								
3.5C x 70 Sq mm (18 GI Strips - 4.0 x 0.8mm)								

		3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)		(Subject to revalidation once in 2 years)	
		3.5Cx 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	02.11.2027		
		3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)			
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	06.02.2025		
		3.5C x 300 Sq mm (32 GI Strips - 4.0 x 0.8mm)	03.11.2027		
		3.5C x 400 Sq mm (39 GI Strips - 4.0 x 0.8mm)			
8	M/s Finolex Cables Limited, 26/27, Mumbai Pune Road, Pimpri, Pune-411 018	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)	27.11.2023 (Subject to revalidation every year)	GM(Q,S&S)/DGM-3/BC-11/19-20/CYS-188 dtd:01.01.2020	
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)			
9	M/s Fortune Art Wires & Cables Pvt Ltd., Plot No: 215/A, phase - II, IDA, Chelapally, Hyderabad - 500051. Ph No: 8374098833. E-mail: smbasha@facables.com	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	21.11.2024	GM(Q,S&S)DGM -3)/ BC-11/19-20/cys-205 dated:04.02.2020 (Subject revalidation every year)	
		10Sqmm, 4Core,(10 GI Strips- 4.0 x 0.8mm)			
		16 Sqmm, 4 Core,(11 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 3.5 Core,(12 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 4 Core,(13 GI Strips - 4.0 x 0.8mm)			
		35 Sqmm, 3.5Core,(14 GI Strips - 4.0 x 0.8mm)			
		50 Sqmm,3.5 Core, (16 GI Strips - 4.0 x 0.8mm)			
		70 Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)			
		95 Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)			
		120 Sqmm, 3.5Core,(23 GI Strips- 4.0 x 0.8mm)			
		150 Sqmm, 3.5 Core, (25 GI Strips-4.0 x 0.8mm)			
		185 Sqmm, 3.5Core,(28 GI Strips - 4.0 x 0.8mm)			
		300 Sqmm, 3.5 Core,(32 GI Strips- 4.0 x 0.8mm)			
		400 Sqmm, 3.5 Core,(39 GI Strips- 4.0 x 0.8mm)			
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)			
		10Core, 2.5 Sqmm, 28 No GI Wires (1.6mm)	13.12.2023		
10	Registered Office: 204&205, Shivam House, Karpura, Commercial Complex, New Delhi-15 (Factory Unit: E-418 to E-421, Industrial Area Chopanki, Biwadi Distt. Alwar(Rajasthan)-301019.	1.1kV LT, XLPE PVC extruded Inner Sheath armoured LT UG cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975		GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-49 dated:19.06.2020 (Subject revalidation every year)	
		300Sq mm, 3.5Core (32GI Strips - 4.0 x 0.8mm)	05.07.2024		
11	M/s Prime Cable Industries Pvt Ltd., E-894, 895, D.S.I.L.D.C. Industrial Area, Narela, Delhi - 110040 Ph No:011-27318598, E-mail:info@primecableindia.com, primecableindustries@gmail.com	1.1kV XLPE or Heat resistance PVC Insulated PVC extruded inner sheath Armoured LT UG Cable	11.06.2025	GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-142 dated:17.10.2020 (Subject revalidation every year)	04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021
		2C x 10 sqmm			
		4C x 10sq mm			
		4C x 16sq mm			
		4C x25sq mm			
		4C x 50sq mm			
		4C x 95sq mm			
		3.5C x 50sq mm			
		3.5C x 70 sq mm			
		3.5C x 95 sq mm			
		3.5C x 120 sq mm			
		3.5C x 150sq mm			
		3.5C x 240sq mm			
		1.1kV class Heat Resistant or PVC Insulated and Unsheathed Aluminium Wires Multistrand Single Core Lead Wires			
		1C x 16 sqmm			
		1C x 25 sqmm			
		1C x 35 sqmm			
		1C x50 sqmm			
		1C x 70 sqmm			
		1C x 95 sqmm			
		1C x 120 sqmm			
		1C x 150 sqmm			
		1C x 185 sqmm			
		1C x 240 sqmm	30.11.2025		04.10.2023 GM(Q,S&S)DGM -3)/ BC-11/21-22/cys-98 dated:04.10.2021
12	M/s Shanti Insulated Cable Co., C/o. Arihant Cable Corporation, No:B-24/1, JHILMIL Industrial Area, Shahdara, Delhi 110095 (Ph No:931177331)	2C x 4sq mm to 3.5C x 400sq mm PVC Insulated and sheathed armour cable with Aluminium conductor	12.03.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-06 dated:13.04.2018 (Subject revalidation every year)	12.03.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-201 dated:23.12.2020
		2Cx 0.5sq mm to 4C x 185sq mm PVC insulated and sheathed flexible cable of copper conductor			
13	M/s Keli Flex Cables, C/o. Arihant Cable Corporation, No: A-34 2nd Floor ,Jhimil	1C x 0.5sq mm to 1C x 400sq mm PVC Insulated sheathed flexible cable with copper conductor	23.01.2023	GM(Q,S&S)DGM -4)/ BC-11/18-19/cys-07 dated:13.04.2018	23.01.2023 GM(Q,S&S)DGM -3)/ BC-11/20-21/cys-183

	Corporation, No. 11/1, 2nd Floor, Gurgaon, Indl. Area, Shadara, Delhi - 110095.	2C x 0.5sq mm to 24C x 0.5sq mm PVC Insulated Unsheathed flexible cable with copper conductor		17/23/2019 dated:10.12.2019 (Subject revalidation every year)	11/20 21/23/200 dated:09.12.2020
14	M/s SPM Power & Telecom Pvt Ltd., Regd Office : Plot NoA-28/1/12, Road No.15, I.D.A., Nacharam, Hyderabad - 500076 (Factory Unit: Sy No.245 & 246, Ramanthapur Village, Chegunta, Yelsurthy Mandal) Contact No: 91 40 29702652, 29702657 E-mail: info@spmcables.in	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	06.12.2025	GM(Q,S&S)DGM -3/ BC-11/21-22/cys-129 dated:07.12.2021	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3C x 400 Sqmm (51 GI Wires - 4mm Dia)			
		1.1kV LT, XLPE PVC extruded Inner Sheath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1, Armouring stripthickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS-3975			
		10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm)			
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)			
		50 Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)			
		25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm)			
		70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm)			
		95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)	25.01.2026	GM(Q,S&S)DGM -3/ AE/BC-11/22-23/cys-12 dated:10.05.2022 (Subject to revalidation once in 2 years)	
		120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)			
		150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm)			
		185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)			
		240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)			
		300 Sqmm, 3.5 Core, (32 GI Strips - 4.0 x 0.8mm)			
		400 Sqmm, 3.5 Core, (39 GI Strips - 4.0 x 0.8mm)			
		1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010			
		PVC Wire - 16Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
		PVC Wire - 25Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs			
		PVC Wire - 50Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs			
		PVC Wire - 95Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs			
		PVC Wire - 120Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs			
		PVC Wire - 185Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs			
		PVC Wire - 240Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs			
		1.1kV Class HR (Heat Resistant) PVC Insulated, Copper Control cables as per IS-554 (Part-1)			
		2Core, 2.5Sqmm, 18 No GI Wires (1.4mm)			
		4Core, 2.5Sqmm, 21 No GI Wires (1.4mm)			
		4Core, 6Sqmm, 25 No GI Wires (1.6mm)	22.01.2026	GM(QS&S)/DGM-3/BC-11/20-21/CYS-229 dtd:22.01.2021	
	M/s SBEE Cables (India), Ltd, No:29,	4 Core, 10Sqmm, 28 No GI Wires (1.6mm)			

15	J.C.W Industrial estate Kanakapura Road, B'lore-64 (Ph No: 080-26662172, 26860166)	<p>19Core, 2.5Sqmm, 36 No GI Wires (1.6mm)</p> <p>1.1kV LT, Heat resistant PVC insulated, PVC extruded Inner Seath armoured UG LT cable as per IS-1554 (Part-1) or IS-7098 Part-1,</p> <p>50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</p> <p>16Sqmm, 4Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>25Sqmm, 4Core, (13 GI Strips - 4.0 x 0.8mm)</p> <p>1.1kV LT, XLPE Copper/Aluminium UG cable IS-7098 Part - 1</p> <p>50Sqmm, 3.5 Core, (16 GI Strips - 4.0 x 0.8mm)</p> <p>70Sqmm, 3.5 Core,(18 GI Strips - 4.0 x 0.8mm)</p> <p>95Sqmm, 3.5 Core,(21 GI Strips - 4.0 x 0.8mm)</p> <p>185Sqmm, 3.5 Core,(28 GI Strips - 4.0 x 0.8mm)</p> <p>240Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)</p> <p>400Sqmm, 3.5 Core,(39 GI Strips - 4.0 x 0.8mm)</p> <p>16Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)</p> <p>3CX95sq.mm (54 GI Wires - 2.5mm Dia)</p> <p>3CX240sq.mm (55 GI Wires - 3.15mm Dia)</p> <p>3CX400sq.mm (51 GI Wires - 4mm Dia)</p>			
16	M/s Vikas Cable Company, No.13, Haiderpur Delhi - 110088 Contact No: 91-11-27495529 E-mail:info@vikascable.com	<p>1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as per IS - 3975</p> <p>16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)</p> <p>25 Sqmm, 4 Core, (13 GI Strips - 4.0 x 0.8mm)</p> <p>70 Sqmm, 3.5 Core, (18 GI Strips - 4.0 x 0.8mm)</p> <p>95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)</p> <p>120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)</p> <p>150 Sqmm, 3.5 Core, (25 GI Strips - 4.0 x 0.8mm)</p> <p>185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)</p> <p>240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)</p> <p>1.1kV LT, XLPE Insulated, PVC Extruded Inner Sheathed armoured UG LT cable as per IS-1554 (Part -1) or IS - 7098 Part -1, Armouring Strip, thickness in average ± 5% resistivity 14ohm/kms (Max) as per IS - 3975</p> <p>50 Sqmm, 4 Core, (17 GI Strips - 4.0 x 0.8mm)</p> <p>400 Sqmm, 3.5 Core , (39 GI Strips - 4.0 x 0.8mm)</p> <p>1.1KV Class HR (Heat Resistant) PVC Insulated & UnSheathed Aluminium Wires Multistrand Single core Lead wires as per IS-694: 2010</p> <p>PVC Wire - 50 Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs</p> <p>PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs</p>	24.12.2027	GM(QS&S)/DGM(EI)-3/BC-11/21-22/CYS-167 dtd:21.02.2022 (Subject to revalidation once in 2 years)	07.01.2025 BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-107 dtd:07.01.2023
17	M/s Gloster Cables Limited, Registered Office: No.183/184, (5-3-370 to 372A) 2nd Floor, Above Mody Motors, Rahtrapathi Road, Secunderabad-500003 Sy No: 310/E, NH-7, Kallakal Village, Toopran Mandal, Dist., Medak (A.P)-502334 Ph No: 9180-22129305, 91-8454250511/12,	<p>11kV, 3Core, HT XLPE UG Cable withpressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)</p> <p>3CX95sq.mm (54 GI Wires - 2.5mm Dia)</p>	12.03.2026	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-107 dtd:07.01.2023 (Subject to revalidation once in 2 years)	19.08.2024 GM(Q,S&S)DGM -3/BC-11/19-20/cys-95 dated:23.08.2019 (subject to revalidation every year) GM(Q,S&S)DGM -3/AE/ BC-11/22-23/cys-137 dated: 09.03.2023

	Z:0/69/11 Email-gclbanglore@glostercable.com, info@glostercable.com	3CX240sq.mm (55 GI Wires - 3.15mm Dia)	20.08.2026	GM(QS&S)/DGM-3/BC-11/21-22/CYS-127 dtd:26.11.2021 (subject to revalidation once in 2 years)	
		3CX400sq.mm (51 GI Wires - 4mm Dia)			
18	M/s Paragon Power cable Ltd., Plot No: 60, Phase -1, HSIIDC Industrial Estate, Kundli, Sonapat, Haryana - 131028 Contact No: 91-9810049100 & 9811025711 E-mail: sales@paragoncables.com	1.1KV, LT XLPE, insulated, PVC extruded Inner Sheath armoured UG LT cable, confirming to IS-1554 (Part-1) or IS-7098 Part-1, Armouring strip, thickness in average ±5% and resistivity 14Ohms/Kms (Max) as per IS-3975			
		240 sqmm, 3.5 Core (30 GI Strips - 4.0x0.8mm)	30.12.2025	GM(QS&S)/AE/BC-11/21-22/CYS-145 dtd: 31.12.2021 (Subject to first revalidation dated before 30.12.2022 and then it will be revalidated once in 2 years)	
		16 sqmm, 4 Core (11 GI Strips - 4.0x0.8mm)			
19	M/s Tirupati Plastomatics Pvt Ltd., B-141A, Road No.9-D, V.K.I. Area, Jaipur - 302013, Rajasthan Ph No: 911412331030, 9060906069, 9351507656 E-mail:contact@tirupatiplastomatics.com	11kV, 3Core, HT XLPE UG Cable with pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	28.07.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-39 dtd:28.07.2022	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3CX400sq.mm (51 GI Wires - 4mm Dia)			
20	M/s Insucon Cables & cond.(P)Ltd., #314-A, 3rd Floor, City centre, Sansar Chandra Road, Jaipur - 302001(Raj) & Factory Unit: No:5A, F-61-63, Bindayaka Industrial Area, Jaipur - 12. E-mail: marketing@insuconcables.com	1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975	22.07.2027		
		4C x 50 Sqmm, (17 GI Strips - 4.0 x 0.8mm)			
		4C x 16 Sqmm, (11 GI Strips - 4.0 x 0.8mm)			
		4C x 25 Sqmm (13 GI Strips - 4.0 x 0.8mm)			
		3.5C x 95 Sqmm, (21 GI Strips - 4.0 x 0.8mm)			
		3.5C x 150 Sqmm, (25GI Strips-4.0 x 0.8mm)			
		3.5C x 240Sqmm, (30 GI Strips - 4.0 x 0.8mm)			
		3.5C x 300 Sqmm, (32 GI Strips - 4.0 x 0.8mm)			
		3.5C x 400 Sqmm, (39 GI Strips - 4.0 x 0.8mm)			
		1.1kV Class HR (Heat Resistant) PVC insulated & Unsheathed Aluminium Wires Multistrand Single core Lead wires as per IS - 694: 2010		BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-78 dtd: 08.11.2022 (subject to revalidation once in 2 years)	
		PVC Wire - 25 Sqmm Al Wt: 6.7 Kgs, Total Wt: 11.5Kgs for 100Mtrs	22.07.2027		
		PVC Wire - 16 Sqmm Al Wt: 4.2 Kgs, Total Wt: 7.5Kgs for 100Mtrs			
		PVC Wire - 50 Sqmm Al Wt: 13.8 Kgs, Total Wt: 22 Kgs for 100Mtrs			
		PVC Wire - 95 Sqmm Al Wt: 25 Kgs, Total Wt: 36Kgs for 100Mtrs			
		PVC Wire - 120 Sqmm Al Wt: 32 Kgs, Total Wt: 45.5Kgs for 100Mtrs			
		PVC Wire - 150 Sqmm Al Wt: 41.4 Kg, Total Wt: 57 Kg/100 Mtrs			
		PVC Wire - 185 Sqmm Al Wt: 49 Kgs, Total Wt: 68Kgs for 100Mtrs			
		PVC Wire - 240 Sqmm Al Wt: 63.5 Kgs, Total Wt: 87Kgs for 100Mtrs			
		11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	25.02.2027	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3C x 400 Sq mm, (51 GI Wires - 4mm Dia)	12.07.2024		

21	M/s Havells India Ltd., 5th Floor, the estate, # 121-Dickenson road, Bangalore-560 042, INDIA (Factory Unit: A-461/462 & SP-215,MIA, Alwar, Rajasthan- 301 030) Contact No: 9036992727 (E-mail:venkataraju.kt@havells.com)	1.1kV LT, XLPE, PVC extruded Inner Seath armoured UG LT cable as per IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		4C x 10 sq mm (10 GI Strips - 4.0 x 0.8mm)	10.01.2024	GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	
		4C x 16 sq mm (11 GI Strips - 4 x 0.8 mm)	07.04.2027	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)	
		4C x 50 sq mm (17 GI Strips - 4.0 x 0.8mm)			
		3.5C x 35 sq mm (14 GI Strips - 4.0 x 0.8mm)	31.01.2024	GM(Q,S&S)DGM -3)/BC-11/18-19/cys-69 dated:18.07.2019 (Subject revalidation every year)	
		3.5C x 50 Sqmm, (16 GI Strips - 4 x 0.8 mm)	07.04.2024		
		3.5C x 70 Sqmm, (18 GI Strips - 4 x 0.8 mm)			
		3.5C x 95 sq mm (21 GI Strips - 4.0 x 0.8mm)	10.01.2024	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)	
		3.5C x 150 sq mm (25 GI Strips - 4.0 x 0.8mm)	29.01.2024		
		3.5C x120 sq mm (23 GI Strips - 4.0 x 0.8mm)	07.04.2027		
		3.5C x185 sq mm (28 GI Strips - 4.0 x 0.8mm)	11.01.2024		
		3.5C x 240 sq mm (30 GI Strips - 4.0 x 0.8mm)	10.01.2024		
		3.5C x 300 Sqmm, (32 GI Strips - 4 x 0.8 mm)	07.04.2027		BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-54 dtd:12.09.2022 (subject to revalidation once in 2 years)
		3.5C x 400 Sqmm, (39 GI Strips - 4 x 0.8 mm)			
22	M/s Apar Industries Limited, (Unit: Uniflex Cables) No: 301/306, Panorama complex R.C Dutt road, Vadodara 390007 (Factory Unit: Plot No: 158/163, GIDC, Umargaon Dist., Valsad, Gujarat – 396171) Contact No:91(080)23443932 /9986049678 E-mail:kr.sanjaya@apar.com	6.35/11kV HT XLPE UG Cable			
		3x95 sq.mm, 3x240sq mm & 3x400sq mm, 11kV HT XLPE U.G. Cable	30.07.2025	GM(Q,S&S)DGM -3)/BC-11/20-21/cys-140 dated:15.10.2020 (subject to revalidation every year)	
		11kV, 3 Core, HT XLPE UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	28.03.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-65 dtd:28.09.2022	
3CX240sq.mm (55 GI Wires - 3.15mm Dia)					
3C x 400 Sq mm, (51 GI Wires - 4mm Dia)					
23	M/s Vardhman Cables & Conductors., 129/C, Shinoli(B.K),Taluk:Chandgad, Dist :Kolhapur, Maharashtra - 416507 Contact No: (02320) 236444/ 236482 E-mail: bharatcab@gmail.com	1.1kV LT, XLPE, PVC extruded Inner Sheath armoured UG LT cable as IS-7098-part 1, Armouring strip thickness in average ± 5% and resistivity 14 Ohms/Kms (Max) as per IS 3975			
		10 Sqmm, 4 Core, (10 GI Strips - 4.0 x 0.8mm)	03.09.2023	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-72 dtd:18.10.2022	
		16 Sqmm, 4 Core, (11 GI Strips - 4.0 x 0.8mm)			
		95 Sqmm, 3.5 Core, (21 GI Strips - 4.0 x 0.8mm)			
		120 Sqmm, 3.5 Core, (23 GI Strips - 4.0 x 0.8mm)			
		185 Sqmm, 3.5 Core, (28 GI Strips - 4.0 x 0.8mm)			
		240 Sqmm, 3.5 Core, (30 GI Strips - 4.0 x 0.8mm)			
300 Sqmm, 3.5 Core , (32 GI Strips - 4.0 x 0.8mm)					
24	M/s Dynamic Cables Ltd, Registered office: F-260, Road No.13, VKI Area, Jaipur-302013 Unit III- H-581A-592A, Road No:6, VKI Area, Jaipur-302013 Contact No: 911412262589, 4042005 E-mail: info@dynamiccables.co.in	11kV, 3 Core, HT UG Cable pressure extruded, inner sheath ROUND WIRE ARMOURED as per IS-7098 (Part-2)			
		3CX95sq.mm (54 GI Wires - 2.5mm Dia)	24.12.2026	BESCOM/GM(QS&S)/DGM-3/AE/BC-11/22-23/CYS-74 dtd:19.10.2022(Subject to revalidation once in 2 years)	
		3CX240sq.mm (55 GI Wires - 3.15mm Dia)			
		3C x 400 Sqmm, (51 GI Wires - 4mm Dia)	23.01.2025		